



APC Back-UPS Pro 1200 - UPS - AC 230 V

720 Watt - 1200 VA - USB - output connectors: 6

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	BR1200G-GR
EAN/UPC	0731304286837

Description

Patent-pending operating mode that bypasses unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection. Battery failure notification provides early-warning fault analysis on batteries enabling timely preventive maintenance. Reserves power capacity and run time for connected equipment that require battery back-up while providing surge only protection for less critical equipment. Cold-start capable provides temporary battery power when the utility power is out. Hot-swappable batteries ensure clean, uninterrupted power to protected equipment while batteries are being replaced. Dataline surge protection provides protection of connected equipment from power surges on the data lines.

Main features

Product Description	APC Back-UPS Pro 1200 - UPS - 720 Watt - 1200 VA
Device Type	UPS - external
Weight	13 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Capacity	720 Watt / 1200 VA
Input Connectors	1 x power CEE 7/7
Output connectors	3 x power CEE 7/7 (UPS and surge) 3 x power CEE 7/7 (surge)
Battery	Lead Acid
Battery Form Factor	Internal
Batteries Qty	1
Run Time (Up To)	5 min at full load



Networking	USB
Dimensions (WxDxH)	11.2 cm x 38 cm x 30.1 cm

Extended details

General	
Device Type	UPS - external
Battery Enclosure Type	Internal
Power Device	
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Frequency Provided	50/60 Hz
Frequency Required	50/60 Hz
Input Connectors	1 x power CEE 7/7
Power Output Connectors Details	3 x power CEE 7/7 (UPS and surge) 3 x power CEE 7/7 (surge)
Output Voltage	AC 230 V 50/60 Hz
Power Capacity	720 Watt / 1200 VA
Dataline Surge Protection	Network - RJ-45 Phone line - RJ-11
Output Waveform	Stepped approximation to a sinewave
Surge Suppression	Yes
Surge Energy Rating	420 Joules
Circuit Protection	Circuit breaker
Battery	
Quantity	1
Technology	Lead Acid
Run Time (Up To)	5 min at full load 18 min at half load
Recharge Time	8 hours
Networking	
Remote Management Interface	USB
Expansion / Connectivity	
Interfaces	1 x management (USB)
Miscellaneous	
Cables Included	USB cable - external Power cable - integrated - 1.8 m
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), cold-start function
Compliant Standards	NEMKO, RoHS, REACH
Software / System Requirements	
Software Included	APC PowerChute Personal Edition
Manufacturer Warranty	
Service & Support	Limited warranty - replace or repair - 2 years



Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	45 dBA

Dimensions & Weight

Width	11.2 cm
Depth	38 cm
Height	30.1 cm
Weight	13 kg

Dimensions & Weight (Shipping)

Shipping Width	23.5 cm
Shipping Depth	49 cm
Shipping Height	39 cm
Shipping Weight	13.8 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.