



APC Back-UPS BX Series BX2200MI-GR

UPS - AC 230 V - 1200 Watt - 2200 VA - 9 Ah - output connectors: 4

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	BX2200MI-GR
EAN/UPC	0731304410881

Description

APC Back-UPS BX series is a cost-effective power protection solution for home and home office environments. The series comprehensive VA range with premium features further enables single UPS capabilities.

Main features

Product Description	APC Back-UPS BX Series BX2200MI-GR - UPS - 1200 Watt - 2200 VA
Device Type	UPS - external
Weight	12.3 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V \pm 10%
Power Capacity	1200 Watt / 2200 VA
Input Connectors	1
Output connectors	4 x power Type F
Battery	Lead Acid - 9 Ah
Batteries Qty	2
Run Time (Up To)	8.5 min at half load
Dimensions (WxDxH)	14 cm x 39 cm x 19 cm

Extended details

General

Device Type	UPS - external
Power Device	
UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 140 - 300 V
Frequency Provided	50/60 Hz
Frequency Required	50/60 Hz
Input Connectors	1



Output Voltage	AC 230 V ± 10% - 50/60 Hz
Power Capacity	1200 Watt / 2200 VA
Dataline Surge Protection	Network - RJ-45 - 1 input line / 1 output line
Output Waveform	Stepped approximation to a sinewave
Surge Energy Rating	273 Joules
Circuit Protection	Circuit breaker

Battery

Quantity	2
Technology	Lead Acid
Voltage Provided	12 V
Capacity	9 Ah
Run Time (Up To)	8.5 min at 50% load 1 min at full load
Recharge Time	8 hours
Transfer Time	6 ms
Features	Maintenance free, sealed

Expansion / Connectivity

Interfaces	1 x USB
------------	---------

Miscellaneous

Cables Included	Power cable - external - 1.2 m
Features	Audible alarm, Automatic Voltage Regulation (AVR)
Compliant Standards	CB, IEC 62040-2, IP20, IEC 62040-1, EN 62040-1

Software / System Requirements

Software Included	APC PowerChute Personal Edition
-------------------	---------------------------------

Manufacturer Warranty

Service & Support	Limited warranty - replace or repair - 2 years
-------------------	--

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%

Dimensions & Weight

Width	14 cm
Depth	39 cm
Height	19 cm
Weight	12.3 kg

Dimensions & Weight (Shipping)

Shipping Width	23.5 cm
Shipping Depth	49.5 cm
Shipping Height	29.7 cm
Shipping Weight	13.3 kg