



## APC Smart-UPS SMT1000IC - UPS

AC 220/230/240 V - 700 Watt - 1000 VA - RS-232 - USB - output connectors: 8 - black - with APC SmartConnect

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT1000IC
EAN/UPC	0731304332978

### Description

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

### Main features

Product Description	APC Smart-UPS SMT1000IC - UPS - 700 Watt - 1000 VA - with APC SmartConnect
Device Type	UPS - external
Weight	18.86 kg
Input Voltage	AC 220/230/240 V
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	700 Watt / 1000 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	8 x power IEC 60320 C13   2 x IEC jumper
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	5.8 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	17.1 cm x 43.9 cm x 21.9 cm
Bundled with	APC SmartConnect

### Extended details

General	
Device Type	UPS - external
Colour	Black
Bundled with	APC SmartConnect
Power Device	



UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	50/60 Hz $\pm$ 3Hz
Frequency Required	50/60 Hz $\pm$ 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	8 x power IEC 60320 C13   2 x IEC jumper
Output Voltage	AC 230 V $\pm$ 5% - 50/60 Hz
Power Capacity	700 Watt / 1000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker
<b>Battery</b>	
Quantity	1
Technology	Lead Acid
Run Time (Up To)	5.8 min at full load   19.1 min at half load   183 min at 50 Watts   100 min at 100 Watts   45.2 min at 200 Watts   24.7 min at 300 Watts   15 min at 400 Watts   9.8 min at 500 Watts   7.1 min at 600 Watts   5.8 min at 700 Watts
Recharge Time	3 hours
Transfer Time	6 ms
Features	Maintenance free, sealed, leak-proof
<b>Networking</b>	
Remote Management Interface	RS-232, USB
<b>Expansion / Connectivity</b>	
Interfaces	1 x management (RS-232)   1 x USB   1 x EPO (emergency power off)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
<b>Miscellaneous</b>	
Cables Included	Serial cable - external   USB cable - external
Features	Audible alarm, emergency power off, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards	CSA, UL 1778, VDE, IEC 62040-2, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1
<b>Software / System Requirements</b>	
Software Included	APC PowerChute Business Edition
<b>Manufacturer Warranty</b>	
Service & Support	Limited warranty - replace or repair - 3 years   Limited warranty - batteries - 2 years
<b>Environmental Parameters</b>	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	41 dBA



<b>Dimensions &amp; Weight</b>	
Width	17.1 cm
Depth	43.9 cm
Height	21.9 cm
Weight	18.86 kg
<b>Dimensions &amp; Weight (Shipping)</b>	
Shipping Width	32.8 cm
Shipping Depth	59.5 cm
Shipping Height	37.6 cm
Shipping Weight	22.77 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.