

APC Smart-UPS Li-Ion 750VA Short Depth with SmartConnect

UPS (rack-mountable / external) - AC 230 V - 600 Watt - 750 VA - RS-232 - USB - output connectors: 6 - 2U - black - for P/N: AR106V - AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432



Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMTL750RMI2UC
EAN/UPC	0731304407966

Description

APC Smart-UPS Li-Ion 750VA Short Depth with SmartConnect - UPS (rack-mountable / external) - AC 230 V - 600 Watt - 750 VA - RS-232, USB - output connectors: 6 - 2U - black - for P/N: AR106V, AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432

Main features

Product Description	APC Smart-UPS Li-Ion 750VA Short Depth with SmartConnect - UPS - 600 Watt - 750 VA
Device Type	UPS - rack-mountable / external
Rack Size	2U
Weight	17.69 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	600 Watt / 750 VA
Input Connectors	Power IEC 60320 C14
Output connectors	6 x power IEC 60320 C13
Battery	Lithium ion
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	43.8 cm x 31.8 cm x 8.6 cm
Designed For	P/N: ACCS1001, ACDC1015, ACDC1019, AP5607, AP9290, AR106V, AR204A, AR3150SP2, AR3300W, AR3350W, AR3357X610, AR3357X617, AR4018A, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432

Extended details

General	
Device Type	UPS - rack-mountable / external

Height (Rack Units)	2U
Colour	Black
	Power Device
UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	50/60 Hz ± 3Hz
Frequency Required	50/60 Hz ± 3Hz
Input Connectors	Power IEC 60320 C14
Power Output Connectors Details	6 x power IEC 60320 C13
Output Voltage	AC 230 V ± 5% - 50/60 Hz
Power Capacity	600 Watt / 750 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	645 Joules
	Battery
Technology	Lithium ion
Recharge Time	3 hours
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x management (RS-232) - RJ-45 1 x management (USB)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
	Miscellaneous
Features	Audible alarm, LCD display
Compliant Standards	NOM, UL 1449, UL 1778, CSA C22.2 No. 107.1, RoHS, FCC Part 15 A, REACH, IP20
	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Manufacturer Warranty
Service & Support	Limited warranty - 5 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)
Sound Emission	45 dB
	Dimensions & Weight
Width	43.8 cm
Depth	31.8 cm

Height	8.6 cm
Weight	17.69 kg
Dimensions & Weight (Shipping)	
Shipping Width	58.4 cm
Shipping Depth	47.2 cm
Shipping Height	22.9 cm
Shipping Weight	18.6 kg
Compatibility Information	
Designed For	P/N: ACCS1001, ACDC1015, ACDC1019, AP5607, AP9290, AR106V, AR204A, AR3150SP2, AR3300W, AR3350W, AR3357X610, AR3357X617, AR4018A, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432

Technical data © 1WorldSync. Subject to technical modifications and errors.