APC Smart-UPS X 750 Rack/Tower LCD

UPS (rack-mountable) - AC 230 V - 600 Watt - 750 VA - output connectors: 8 - 2U - black

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMX750I
EAN/UPC	0731304268581

Description

Attach the device to an emergency power off (EPO) system so that power can be turned off in an emergency situation. Green mode bypasses unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection. High frequency design reduces or eliminates bulky transformers resulting in lighter units for ease of handling. Energy meter provides actual kilowatt hours of usage for energy conscious users. Intuitive LCD interface provides clear and accurate information with the ability to configure the UPS locally with easy to use navigation keys. UPS recognizes when external battery packs are attached and automatically adjusts runtime. Multiple outlet groups may be controlled separately from the UPS for discrete reboot of hung devices, sequenced on / off and non-critical load shedding.

Main features

Product Description	APC Smart-UPS X 750 Rack/Tower LCD - UPS - 600 Watt - 750 VA
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	22.1 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V ± 5%
Power Capacity	600 Watt / 750 VA
Input Connectors	Power IEC 60320 C14
Output connectors	8 x power IEC 60320 C13
Battery	Lead Acid
Run Time (Up To)	14.2 min at full load
Colour	Black
Dimensions (WxDxH)	8.9 cm x 49 cm x 43.2 cm

Extended details

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
	Power Device
UPS Technology	Line interactive
Power Modules Qty	1
Input Voltage	AC 230 V
Frequency Provided	47 - 63 Hz
Frequency Required	50/60 Hz
Input Connectors	Power IEC 60320 C14
Power Output Connectors Details	8 x power IEC 60320 C13
Output Voltage	AC 230 V ± 5% - 47 - 63 Hz
Power Capacity	600 Watt / 750 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	645 Joules
	Battery
Technology	Lead Acid
Run Time (Up To)	14.2 min at full load ¦ 37.8 min at half load
Recharge Time	3 hours
	Expansion / Connectivity
Expansion Slots	1 (total) / 1 (free) x SmartSlot
	Miscellaneous
Cables Included	Serial cable - external ¦ Power cable - integrated - 1.8 m
Features	Audible alarm, LCD display
Compliant Standards	C-Tick, UL 1449, VDE, EN 50091-2, RoHS Exemption 7b, EN 50091-1
	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years ¦ Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	40 dBA
	Dimensions & Weight
Width	8.9 cm
Depth	49 cm
Height	43.2 cm
Weight	22.1 kg
	Dimensions & Weight (Shipping)
Shipping Width	24.6 cm
Shipping Depth	62 cm

Shipping Height	58.9 cm
Shipping Weight	26.5 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.