



APC Smart-UPS SRT 1500VA - UPS (rack-mountable / external)

AC 220/230/240 V - 1500 Watt - 1500 VA - USB - serial - output connectors: 6 - PFC - black

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SRT1500XLI
EAN/UPC	0731304340300

Description

Battery failure notification provides early-warning fault analysis on batteries enabling timely preventive maintenance. ECO Mode by-passes unused electrical components in good power conditions to achieve high operating efficiency without sacrificing protection. It protects the initial investment in the UPS when migrating from tower to rack-mount environment.

Main features

Product Description	APC Smart-UPS SRT 1500VA - UPS - 1500 Watt - 1500 VA
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Weight	20.5 kg
Input Voltage	AC 220/230/240 V
Output Voltage	AC 220/230/240 V \pm 2%
Power Capacity	1500 Watt / 1500 VA
Input Connectors	Power IEC 60320 C14, power BS 1363A, Europlug (power CEE 7/16)
Output connectors	6 x power IEC 60320 C13
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	5.2 min at full load
Networking	USB, serial
Colour	Black
Dimensions (WxDxH)	8.5 cm x 50.5 cm x 43.2 cm

Extended details

General	
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Colour	Black
Power Device	
UPS Technology	On-line



Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 100 - 275 V
Frequency Provided	50/60 Hz \pm 3Hz
Frequency Required	40 - 70 Hz
Input Connectors	Power IEC 60320 C14, power BS 1363A, Europlug (power CEE 7/16)
Power Output Connectors Details	6 x power IEC 60320 C13
Output Voltage	AC 220/230/240 V \pm 2% - 50/60 Hz
Power Capacity	1500 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	432 Joules
Circuit Protection	Circuit breaker
Efficiency	92% at 100% Load

Battery

Quantity	1
Technology	Lead Acid
Voltage Provided	48 V
Run Time (Up To)	5.2 min at full load 14.2 min at half load
Recharge Time	3 hours
Features	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface	USB, serial
-----------------------------	-------------

Expansion / Connectivity

Interfaces	1 x serial - RJ-45 1 x EPO (emergency power off) 1 x USB
Expansion Slots	1 (total) / 1 (free) x SmartSlot

Miscellaneous

Cables Included	Power cable 1.83 m USB cable - external
Features	Audible alarm, LCD display, internal bypass, cold-start function, firmware upgradable, hot-swappable batteries, Eco-Mode, auto restart
Compliant Standards	REACH, IP20, EAC

Software / System Requirements

Software Included	APC PowerChute Business Edition
-------------------	---------------------------------

Manufacturer Warranty

Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
-------------------	---

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)
Sound Emission	50 dBA

Dimensions & Weight

Width	8.5 cm
Depth	50.5 cm
Height	43.2 cm



Weight	20.5 kg
--------	---------

Dimensions & Weight (Shipping)

Shipping Width	59.4 cm
----------------	---------

Shipping Depth	74.9 cm
----------------	---------

Shipping Height	24.6 cm
-----------------	---------

Shipping Weight	29.6 kg
-----------------	---------

Technical data © CNET Content Solutions. Subject to technical modifications and errors.