



APC Smart-UPS SRT 3000VA - UPS

AC 230 V - 2700 Watt - 3000 VA - RS-232 - USB - output connectors: 10

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SRT3000XLI
EAN/UPC	0731304317678

Description

Smart-UPS On-Line provides high density, true double-conversion on-line power protection for servers, voice / data networks, medical labs, and light industrial applications. Capable of supporting loads from 1 to 20kVA in a rack/tower convertible form, the Smart-UPS On-Line is available from 2U to 12U. Recent family extensions at 15 and 20kVA enable support of power hungry blade servers or heavily loaded equipment racks. When business-critical systems require runtime in hours, not minutes, Smart-UPS On-Line can be configured with matching battery packs to comply with aggressive runtime demands. The included PowerChute management software provides unattended graceful shutdown of network operating systems. All models 5kVA and above include an integrated Network Management Card for remote management (optional on models below 5 kVA). The Smart-UPS On-Line family provides customers with a reliable source of uninterruptible power even in demanding power environments, including very wide input voltage window, extremely tight output voltage regulation, frequency regulation, internal bypass, and input power factor correction.

Main features

Product Description	APC Smart-UPS SRT 3000VA - UPS - 2700 Watt - 3000 VA
Device Type	UPS - external
Weight	31.3 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V \pm 3%
Power Capacity	2700 Watt / 3000 VA
Input Connectors	Power IEC 60320 C20, power BS 1363A, Europlug (power CEE 7/16)
Output connectors	8 x power IEC 60320 C13 2 x power IEC 60320 C19
Battery	Lead Acid
Run Time (Up To)	4 min at full load
Networking	RS-232, USB



Dimensions (WxDxH)	8.5 cm x 63.5 cm x 43.2 cm
Environmental Standards	ENERGY STAR

Extended details

	General
Device Type	UPS - external
	Power Device
UPS Technology	On-line
Input Voltage	AC 230 V
Input Voltage Range	AC 220 - 240 V
Input Voltage Range (Adjustable)	AC 100 - 275 V
Frequency Provided	50/60 Hz
Frequency Required	40 - 70 Hz
Input Connectors	Power IEC 60320 C20, power BS 1363A, Europlug (power CEE 7/16)
Power Output Connectors Details	8 x power IEC 60320 C13 ¦ 2 x power IEC 60320 C19
Output Voltage	AC 230 V ± 3% - 50/60 Hz
Power Capacity	2700 Watt / 3000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	340 Joules
	Battery
Technology	Lead Acid
Recharge Time	3 hours
Features	Maintenance free, sealed, leak-proof
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x serial - RJ-45 ¦ 1 x EPO (emergency power off) ¦ 1 x management (USB)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
	Miscellaneous
Cables Included	3 x power cable 2.44 m
Features	Audible alarm, emergency power off, LCD display, internal bypass
Compliant Standards	VDE, IEC 62040-2, IP20, EAC, RCM, IEC 62040-1
	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Environmental Standards
ENERGY STAR	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years ¦ Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C



Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95% (non-condensing)
Sound Emission	55 dBA

Dimensions & Weight

Width	8.5 cm
Depth	63.5 cm
Height	43.2 cm
Weight	31.3 kg

Dimensions & Weight (Shipping)

Shipping Width	59.9 cm
Shipping Depth	87.1 cm
Shipping Height	24.6 cm
Shipping Weight	36.74 kg

Technical data © CNET Content Solutions. Subject to technical modifications and errors.