

ASUS ProArt PA34VCNV - LED monitor

curved - 34.1" - 3440 x 1440 UWQHD @ 60 Hz - IPS - 300 cd/m² - 1000:1 - HDR10 - 5 ms - 2xHDMI - 2xDisplayPort - USB-C - speakers - black

Group	Printing Accessories
Manufacturer	ASUS
Manufacturer item no.	90LM04A0-B02370
EAN/UPC	4711387206393



Description

ASUS ProArt PA34VCNV - LED monitor - curved - 34.1" - 3440 x 1440 UWQHD @ 60 Hz - IPS - 300 cd/m² - 1000:1 - HDR10 - 5 ms - 2xHDMI, 2xDisplayPort, USB-C - speakers - black

Main features

Product Description	ASUS ProArt PA34VCNV - LED monitor - curved - 34.1" - HDR
Device Type	LED-backlit LCD monitor - 34.1"
Energy Class	Class E
Curved Screen	Yes
Features	USB 3.0/USB-C hub
Panel Type	IPS
Aspect Ratio	21:9
Native Resolution	UWQHD 3440 x 1440 at 60 Hz
Pixel Pitch	0.2325 mm
Brightness	300 cd/m²
Contrast Ratio	1000:1
HDR Capable	HDR10
Response Time	5 ms (grey-to-grey)
Colour Support	1.07 billion colours
Colour Gamut	100% sRGB
Input Connectors	2xHDMI, 2xDisplayPort, USB-C
Display Position Adjustments	Height, swivel, tilt
Screen Coating	Anti-glare
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black

Dimensions (WxDxH) - with stand	81.72 cm x 24 cm x 56.92 cm
Weight	10.8 kg
Environmental Standards	ENERGY STAR Qualified EPEAT Silver
Compliant Standards	VCCI, BSMI, ICES-003, CB, CCC, DOC, PSB, FCC, RoHS, ISO 9241-307, KCC, WEEE, PSE Mark, J-MOSS, E-Standby, CEC, UkrSEPRO, KC, ERP, CECP, CEL, RCM, TUV Rheinland Low Blue Light Certification, CU, TUV Rheinland Flicker Free Certification, HDCP 2.2, HF, Ukraine Energy Label, UL/cUL, TUV-GS, TUV-Ergo

Extended details

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	34.1"
Curved Screen	Yes (3800R)
Built-in Devices	USB 3.0/USB-C hub
Panel Type	IPS
Aspect Ratio	21:9
Native Resolution	UWQHD 3440 x 1440 at 60 Hz
Pixel Pitch	0.2325 mm
Brightness	300 cd/m ²
Contrast Ratio	1000:1
HDR Format	HDR10
Colour Support	1.07 billion colours
Colour Gamut	100% sRGB
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	48 - 60 Hz
Horizontal Refresh Rate	15 - 135 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Features	Picture in picture, picture by picture, HDCP, Trace Free Technology, Flicker Free technology, Adaptive-Sync technology, ASUS ProArt Calibration technology, Low Blue Light technology, ProArt Palette, Delta E=2 colour accuracy, QuickFit Plus

Colour	Black
Dimensions (WxDxH)	81.72 cm x 24 cm x 56.92 cm - with stand
Weight	10.8 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Connectivity
Interfaces	USB-C 2 x USB 3.2 Gen 1 2 x HDMI 2 x DisplayPort Headphones LAN (RJ-45)
	Mechanical
Display Position Adjustments	Height, swivel, tilt
Tilt Angle	-5/+23
Swivel Angle	30
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately)
Compliant Standards	VCCI, BSMI, ICES-003, CB, CCC, DOC, PSB, FCC, RoHS, ISO 9241-307, KCC, WEEE, PSE Mark, J-MOSS, E-Standby, CEC, UkrSEPRO, KC, ERP, CECP, CEL, RCM, TUV Rheinland Low Blue Light Certification, CU, TUV Rheinland Flicker Free Certification, HDCP 2.2, HF, Ukraine Energy Label, UL/cUL, TUV-GS, TUV-Ergo
Security Slot Type	Kensington security slot
	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	26 kWh/1000h
Power Consumption HDR (On mode)	44 kWh/1000h
Power Consumption (Typical)	26.9 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0 Watt
On / Off Switch	Yes
	Software / System Requirements

Included Software	Adobe Creative Cloud (3 months membership)
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 81.72 cm - depth: 9.17 cm - height: 36.97 cm - weight: 7.8 kg With stand - width: 81.72 cm - depth: 24 cm - height: 56.92 cm - weight: 10.8 kg
Dimensions & Weight (Shipping)	
Shipping Width	1.08 m
Shipping Depth	52 cm
Shipping Height	19 cm
Shipping Weight	16.3 kg
Sustainability Information	
EPEAT Compliant	EPEAT Silver
ENERGY STAR Certified	Yes
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Technical data © 1WorldSync. Subject to technical modifications and errors.