

ASUS ROG Loki SFX-L Platinum - Power supply (internal)

ATX 3.0 / SFX-L - 80 PLUS Platinum - AC 100-240 V - 750 Watt

Group	Power Supply
Manufacturer	ASUS
Manufacturer item no.	90YE00N4-B0NA00
EAN/UPC	4711081722915



Description

Taking after the ROG Thor, the ROG Loki SFX-L 750 W Platinum brandishes the same enthusiast-grade components and features, all packed into an SFX-L form factor. Boasting quiet operation and high performance, the Loki is primed to power your next SFF build.

Main features

Product Description	ASUS ROG Loki SFX-L Platinum - power supply - 750 Watt
Device Type	Power supply - internal
Specification Compliance	ATX 3.0 / SFX-L
80 PLUS Certification	80 PLUS Platinum
Weight	1.815 kg
Input Voltage	AC 100-240 V
Output Voltage	+3.3, +5, ±12 V
Power Capacity	750 Watt
Output Current	+3.3V - 20 A +5V - 20 A +12V - 62.5 A -12V - 0.8 A +5VSB - 2.5 A
Output connectors	1 x power 24 pin ATX with detachable 4 pin section 2 x power 8 pin EPS12V with detachable 4 pin ATX12V section 1 x 16 pin PCI Express power 3 x 8 pin PCI Express power 6 x 15 pin Serial ATA power 4 x 4 PIN internal power
Modular Cable Management	Yes
Cooling System	120 mm fan
Included Accessories	SFX to ATX bracket
Dimensions (WxDxH)	12.5 cm x 12.5 cm x 6.35 cm

Extended details

	General
Device Type	Power supply - internal
Specification Compliance	ATX 3.0 / SFX-L
PSU Form Factor	SFX-L
	Power Device

Input Voltage	AC 100-240 V
Power Output Connectors Details	1 x power 24 pin ATX with detachable 4 pin section 2 x power 8 pin EPS12V with detachable 4 pin ATX12V section 1 x 16 pin PCI Express power 3 x 8 pin PCI Express power 6 x 15 pin Serial ATA power 4 x 4 PIN internal power
Output Voltage	+3.3, +5, ±12 V
Power Capacity	750 Watt
Output Current	+3.3V - 20 A +5V - 20 A +12V - 62.5 A -12V - 0.8 A +5VSB - 2.5 A
Efficiency	92%
Modular Cable Management	Yes
80 PLUS Certification	80 PLUS Platinum
	Miscellaneous
Included Accessories	SFX to ATX bracket
Cables Included	AC input cable - external Power 24 pin ATX modular cable 45 cm 2 x power 8 pin +12V with detachable 4 pin section modular cable 55 cm 16-pin 12VHPWR power cable 45 cm 8 pin PCI Express power with detachable 2 pin section modular cable 45 cm 2x 8 pin PCI Express power with detachable 2 pin section modular cable 45 cm ARGB sync cable 80 cm 2 x 3x Serial ATA modular cable 4 pin internal power cable
Cooling System	120 mm fan
Features	Overheat protection, over current protection, over voltage protection, overpower protection, undervoltage protection, short-circuit protection, dual ball bearing cooling fan, fully modular, ASUS Aura Sync, ROG heatsink, Axial-tech fan design, 0db Technology, ARGB fan
Compliant Standards	RoHS
	Manufacturer Warranty
Service & Support	Limited warranty - 10 years Limited warranty - RGB LEDs - 3 years
	Dimensions & Weight
Width	12.5 cm
Depth	12.5 cm
Height	6.35 cm
Weight	1.815 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.