

ASUS VT168HR - LED monitor - 15.6"

touchscreen - 1366 x 768 WXGA @ 60 Hz - TN - 220 cd/m² - 400:1 - 5 ms - HDMI - VGA

Group	Flat Screens
Manufacturer	ASUS
Manufacturer item no.	90LM02G1-B04170
EAN/UPC	4711081368403



Description

ASUS VT168HR - LED monitor - 15.6" - touchscreen - 1366 x 768 WXGA @ 60 Hz - TN - 220 cd/m² - 400:1 - 5 ms - HDMI, VGA

Main features

Product Description	ASUS VT168HR - LED monitor - 15.6"
Device Type	LED-backlit LCD monitor - 15.6" - touchscreen
Energy Class	Class C
Features	USB Hub
Panel Type	TN
Native Resolution	WXGA 1366 x 768 at 60 Hz
Brightness	220 cd/m ²
Contrast Ratio	400:1 / 100000000:1 (dynamic)
Response Time	5 ms (grey-to-grey)
Colour Support	262,000 colours
Input Connectors	HDMI, VGA
Display Position Adjustments	Tilt
Screen Coating	Anti-glare
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - with stand	37.78 cm x 18.94 cm x 28.07 cm
Weight	1.51 kg
Compliant Standards	TUV Rheinland Flicker Free Certification, HDCP 1.4, TUV Rheinland Low Blue Light (Software Solution)

Extended details

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class C

Diagonal Size	15.6"
Built-in Devices	USB Hub
Panel Type	TN
Native Resolution	WXGA 1366 x 768 at 60 Hz
Brightness	220 cd/m ²
Contrast Ratio	400:1 / 100000000:1 (dynamic)
Colour Support	262,000 colours
Response Time	5 ms (grey-to-grey)
Horizontal Viewing Angle	90
Vertical Viewing Angle	60
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Features	HDCP, Trace Free Technology, ASUS Smart Contrast Ratio (ASCR), ASUS QuickFit Virtual Scale, Low Blue Light Mode, Flicker Free technology, ASUS EyeCare Technology, Colour Temperature Selection
Dimensions (WxDxH)	37.78 cm x 18.94 cm x 28.07 cm - with stand
Weight	1.51 kg
	Input
Type	Touchscreen
	Connectivity
Interfaces	VGA HDMI USB upstream
	Mechanical
Display Position Adjustments	Tilt
Tilt Angle	-5/+30
VESA Mounting Interface	75 x 75 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately)
Compliant Standards	TUV Rheinland Flicker Free Certification, HDCP 1.4, TUV Rheinland Low Blue Light (Software Solution)
Security Slot Type	Kensington security slot
	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	7 kWh/1000h
Power Consumption (Typical)	8 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.5 Watt

Dimensions & Weight

Dimensions & Weight Details With stand - width: 37.78 cm - depth: 18.94 cm - height: 28.07 cm - weight: 1.51 kg | Without stand - width: 37.78 cm - depth: 4.4 cm - height: 23.59 cm

Dimensions & Weight (Shipping)

Shipping Width	43.38 cm
Shipping Depth	12.2 cm
Shipping Height	34.97 cm
Shipping Weight	2.93 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.