

CyberPower Systems CyberPower UT1500EG, Line-Interactive, 1.5 kVA, 900 W, Pseudo sine, 167 V, 295 V

Backup UPS for Computer and Peripheral

Group	Power Supply
Manufacturer	CyberPower Systems
Manufacturer item no.	UT1500EG
EAN/UPC	4711027790930



Description

CyberPower UT1500EG guarantees power protection for computers, networking equipment, and storage devices. The product adopts line-interactive topology with Automatic Voltage Regulation (AVR) function to offer stabilized AC power output. The patented GreenPower UPS™ Bypass design achieves ultra-low power consumption to reduce energy costs, and allows a lower operation temperature which extends battery lifespan.

The LED indicator shows the utility, battery and operating status of the UPS. It is also compatible with generators to extend power continuity. Other features include overload protection, EMI filter and configurable alarm to safeguard your devices. Its tower design allows users to place it easily on desks or other tight spaces.

Main features

	General
UPS topology	Line-Interactive
Output power	900 W
Output power capacity	1.5 kVA
AC outlet types	Type F
AC outlets quantity	4 AC outlet(s)
USB port	Yes
USB port type	USB Type A/USB Type-C
Battery technology	Sealed Lead Acid (VRLA)
Battery recharge time	8 h
Charging current	2.1 A
Form factor	Tower
Product colour	Black
Housing material	Plastic
Compliance certificates	CE, RoHS

Extended details

Features

UPS topology	Line-Interactive
Output power capacity	1.5 kVA
Output power	900 W
Waveform	Pseudo sine
Input operation voltage (min)	167 V
Input operation voltage (max)	295 V
Input frequency	50/60 Hz
Output operation voltage (max)	230 V
Automatic Voltage Regulation (AVR)	Yes
Maximum current	6.52 A
Surge energy rating	150 J
Response time	4 ms
Heat dissipation	34.1 BTU/h
EMI/RFI noise filtering	Yes
Noise level	50 dB
Surge protection	Yes
Surge protection features	Modem, Network, Telephone
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
	Design
Form factor	Tower
Product colour	Black
Housing material	Plastic
Cable length	1.5 m
Cooling type	Active
Control type	Buttons
LED indicators	Error, Operation, Yes
	Ports & interfaces
AC outlet types	Type F
AC outlets quantity	4 AC outlet(s)
USB port	Yes
USB port type	USB Type A/USB Type-C
Ethernet LAN (RJ-45) ports	2
Cabling technology	10/100/1000Base-T(X)
	Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery recharge time	8 h
Charging current	2.1 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90 %
Storage relative humidity (H-H)	0 - 90 %
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m
Weight & dimensions	
Width	148 mm
Depth	298 mm
Height	178 mm
Weight	9.1 kg
Packaging content	
Manual	Yes
Quick installation guide	Yes
Certificates	
Compliance certificates	CE, RoHS
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Packaging data	
Package width	271 mm
Package depth	397 mm
Package height	202 mm
Package weight	9.7 kg
Sustainability	
Sustainability compliance	Yes