

D-Link DUB-E250 - Network adapter

USB-C / Thunderbolt 3 - 2.5GBase-T x 1

Group	Interface Cards
Manufacturer	D-Link
Manufacturer item no.	DUB-E250
EAN/UPC	0790069457494



Description

Instantly add multi-Gigabit connectivity to your laptop computer or desktop. Just plug the adapter into an available USB-C port and you're ready to go.

Main features

Product Description	D-Link DUB-E250 - network adapter - USB-C / Thunderbolt 3 - 2.5GBase-T x 1
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	USB-C / Thunderbolt 3
Ports	2.5GBase-T x 1
Dimensions (WxDxH)	5.3 cm x 2.15 cm x 1.5 cm
Weight	28.5 g
Cabling Type	Ethernet 10Base-T, Ethernet 100Base-TX, Ethernet 1000Base-T, Ethernet 2.5GBase-T
Data Link Protocol	10Mb LAN, 100Mb LAN, GigE, 2.5 GigE
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, USB 2.0, USB 3.0, IEEE 802.3az, IEEE 802.3bz, USB 3.1 Gen 1
System Requirements	Apple MacOS X 10.6 or later, Microsoft Windows 7 / 8 / 10

Extended details

	General
Device Type	Network adapter
Form Factor	External
Interface (Bus) Type	USB-C / Thunderbolt 3
	Networking
Ports	2.5GBase-T x 1
Connectivity Technology	Wired
Cabling Type	Ethernet 10Base-T, Ethernet 100Base-TX, Ethernet 1000Base-T, Ethernet 2.5GBase-T
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, 2.5 Gigabit Ethernet
Status Indicators	Link/activity, connection status

Features	Flow control, auto-uplink (auto MDI/MDI-X), full duplex mode, Energy Efficient Ethernet, crossover detection, VLAN Tagging, dynamic power management
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, USB 2.0, USB 3.0, IEEE 802.3az, IEEE 802.3bz, USB 3.1 Gen 1
Expansion / Connectivity	
Interfaces	1 x 1/2.5GBase-T - RJ-45 - female
Miscellaneous	
Cables Included	1 x Thunderbolt 3 / USB-C cable (integrated) - 16 cm
Compliant Standards	IC, FCC
Software / System Requirements	
OS Required	Apple MacOS X 10.6 or later, Microsoft Windows 7 / 8 / 10
Dimensions & Weight	
Width	5.3 cm
Depth	2.15 cm
Height	1.5 cm
Weight	28.5 g
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	45 °C
Humidity Range Operating	10 - 85% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.