



D-Link DGS 108 - Switch - unmanaged

8 x 10/100/1000 - desktop

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-108/E
EAN/UPC	0790069368240

Description

D-Link's DGS-105 and DGS-108 Gigabit Ethernet switches provide a cost-effective way for small and medium sized businesses to create a small network and connect computers, wireless Access Points, IP cameras, network printers and other Ethernet devices quickly and easily without complicated configurations. These switches come with 5 or 8 Gigabit Ethernet ports with an auto-sensing function to detect the maximum speed of the connected devices, allowing you to run your network with the best possible performance. Their fanless design and solid metal housing makes them completely silent so they are ideal for offices, libraries or meeting rooms, and for industrial and hazardous environments like factories and warehouses.

The DGS-105 and DGS-108 are designed with durability and performance in mind. Their sturdy metal housing will protect them against accidental harm, while helping to dissipate heat and to reduce stress on internal components. The LEDs allow for an easy reading of each port status and speed, helping to troubleshoot connectivity problems. For a convenient placement, these switches come with a wall mounting kit and a slot for a Kensington security lock to protect them from theft.

Despite being unmanaged, Plug and Play switches, the DGS-105 and DGS-108 are able to classify network traffic by assessing the 802.1p field in the Ethernet frames, and forward them out of its ports depending on their priority. This allows for a smooth integration of video, voice and data traffic without delays or loss of quality.

The cable diagnostics function enables users to quickly troubleshoot faulty network cables that may lead to transmission errors. At startup, the switch performs a micro-test to assess the quality of the cables connected to its ports. If a fault is detected, the amber LED will lit up. If the cables pass the test, the green LED will be illuminated, indicating that the network is error-free. This feature can save valuable time when trying to single out a faulty cable that causes problems in the whole network.

The DGS-105 and DGS-108 are part of D-Link Green, D-Link's eco-friendly technology, providing energy savings, reduced power consumption, and a longer product lifespan without sacrificing operational performance or functionality. These switches implement the 802.3az Energy Efficient Ethernet (EEE) standard, which can save a substantial amount of energy by detecting the port status, putting them in low-power, stand-by mode when no network traffic is detected. Additionally, the Green Ethernet technology in the DGS-

105/108 can detect the length of the network cables connected to their ports and provide only the right amount of energy required. This helps businesses to save money by reducing their electricity bills with no compromise on performance.

Main features

Product Description	D-Link DGS 108 - switch - 8 ports - unmanaged
Device Type	Switch - 8 ports - unmanaged
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000
Performance	Switching capacity: 16 Gbps
MAC Address Table Size	8K entries
Jumbo Frame Support	9000 bytes
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), packet filtering, store and forward, half duplex mode, full duplex mode, Quality of Service (QoS), Cable Diagnostics Function, D-Link Green Technology, Energy Efficient Ethernet, security lock slot (cable lock sold separately), metal housing
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
Environmental Standards	ENERGY STAR Qualified
Dimensions (WxDxH)	16.2 cm x 10.2 cm x 2.8 cm
Weight	440 g
Localisation	Europe

Extended details

General	
Device Type	Switch - 8 ports - unmanaged
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000
Performance	Switching capacity: 16 Gbps
MAC Address Table Size	8K entries
Jumbo Frame Support	9000 bytes
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), packet filtering, store and forward, half duplex mode, full duplex mode, Quality of Service (QoS), Cable Diagnostics Function, D-Link Green Technology, Energy Efficient Ethernet, security lock slot (cable lock sold separately), metal housing
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
RAM	128 KB
Status Indicators	Power, link/activity
Expansion / Connectivity	
Interfaces	8 x 1000Base-T RJ-45
Power	
Power Device	External power adapter
ENERGY STAR Certified	Yes



Miscellaneous

MTBF	2,053,751 hours
Compliant Standards	Plug and Play, FCC Class B certified, VCCI Class B ITE, cUL, CB, ICES-003 Class B, C-Tick Class B, RoHS
Localisation	Europe

Dimensions & Weight

Width	16.2 cm
Depth	10.2 cm
Height	2.8 cm
Weight	440 g

Manufacturer Warranty

Service & Support	Limited warranty - lifetime
-------------------	-----------------------------

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-10 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 90% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.