

D-Link DGS 1100-08PV2 - Switch

smart - 8 x 10/100/1000 (PoE) - desktop - PoE (64 W)

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1100-08PV2/E
EAN/UPC	0790069467813



Description

D-Link DGS 1100-08PV2 - Switch - smart - 8 x 10/100/1000 (PoE) - desktop - PoE (64 W)

Main features

Product Description	D-Link DGS 1100-08PV2 - switch - 8 ports - smart
Device Type	Switch - 8 ports - smart
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000 (PoE)
Power Over Ethernet (PoE)	PoE
PoE Budget	64 W
Performance	Switching capacity: 16 Gbps Forwarding performance: 11.9 Mpps
MAC Address Table Size	4K entries
Jumbo Frame Support	9216 bytes
Remote Management Protocol	HTTP
Features	Flow control, Layer 2 switching, auto-negotiation, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, Broadcast Storm Control, half duplex mode, full duplex mode, Multicast Storm Control, Unicast Storm Control, Quality of Service (QoS), Cable Diagnostics Function, bandwidth control, D-Link Green Technology, fanless, 1.5MB packet buffer, Weighted Round Robin (WRR), loopback detection, DSCP based QoS
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	17.1 cm x 9.78 cm x 2.86 cm
Weight	430 g

Extended details

General	
Device Type	Switch - 8 ports - smart
Enclosure Type	Desktop
Subtype	Gigabit Ethernet

Ports	8 x 10/100/1000 (PoE)
Power Over Ethernet (PoE)	PoE
PoE Budget	64 W
Performance	Switching capacity: 16 Gbps Forwarding performance: 11.9 Mpps
MAC Address Table Size	4K entries
Jumbo Frame Support	9216 bytes
Remote Management Protocol	HTTP
Features	Flow control, Layer 2 switching, auto-negotiation, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, Broadcast Storm Control, half duplex mode, full duplex mode, Multicast Storm Control, Unicast Storm Control, Quality of Service (QoS), Cable Diagnostics Function, bandwidth control, D-Link Green Technology, fanless, 1.5MB packet buffer, Weighted Round Robin (WRR), loopback detection, DSCP based QoS
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az
Flash Memory	2 MB
Expansion / Connectivity	
Interfaces	8 x 1000Base-T RJ-45 PoE - 30 W
Power	
Power Device	External power adapter
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	77.9 Watt
Power Consumption Stand by	2 Watt
Miscellaneous	
MTBF	786,841 hours
Compliant Standards	FCC Class B certified, BSMI, cUL, CB, LVD, VCCI Class B, RoHS 10
Software / System Requirements	
Software Included	D-Link Network Assistant
Dimensions & Weight	
Width	17.1 cm
Depth	9.78 cm
Height	2.86 cm
Weight	430 g
Manufacturer Warranty	
Service & Support	Limited warranty - lifetime
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 90% RH (non-condensing)
Min Storage Temperature	-40 °C
Max Storage Temperature	70 °C

Humidity Range Storage

0 - 95% RH (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.