

D-Link DGS 1210-10MP - Switch

L2+ - smart - 8 x 10/100/1000 (PoE+) + 2 x Gigabit SFP - desktop - rack-mountable - PoE+ (130 W)

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1210-10MP/E
EAN/UPC	790069467714



Description

D-Link DGS 1210-10MP - Switch - L2+ - smart - 8 x 10/100/1000 (PoE+) + 2 x Gigabit SFP - desktop, rack-mountable - PoE+ (130 W)

Main features

Product Description	D-Link DGS 1210-10MP - switch - 10 ports - smart - rack-mountable
Device Type	Switch - 10 ports - L2+ - smart
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000 (PoE+) + 2 x Gigabit SFP
Power Over Ethernet (PoE)	PoE+
PoE Budget	130 W
Performance	Switching capacity: 20 Gbps Forwarding performance (64-byte packet size): 14.88 Mpps
Capacity	Static MAC entries: up to 256 IPv4 routes: 124 IPv6 routes: 50
MAC Address Table Size	8K entries
Jumbo Frame Support	10000 bytes
Routing Protocol	IGMP, IGMPv2, IGMPv3, MLD, MLDv2, static IP routing
Remote Management Protocol	CLI, Telnet, TFTP, SNMP 1, SNMP 3, SNMP 2c, RMON 1, SSH-2, HTTP
Features	Full duplex capability, auto-uplink (auto MDI/MDI-X), 4.1Mbit packet buffer, loopback detection, LLDP support, LLDP-MED, STP support, RSTP support, MSTP support, flow control, port mirroring, Multicast filtering function, Asymmetric VLAN, auto voice VLAN, QoS, WRR, Extensive ACL support, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, Safeguard Engine, DoS attack prevention, anti-ARP spoofing, DHCP snooping, BOOTP support, DHCP client, fanless, store and forward, D-Link Green Technology
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3az, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1p, IEEE 802.1Q, IEEE 802.1D, IEEE 802.1s, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.1ab (LLDP)

Power	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH)	33 cm x 18 cm x 4.4 cm
Weight	1.77 kg
Localisation	Europe

Technical data © 1WorldSync. Subject to technical modifications and errors.