

D-Link Web Smart DGS-1210-20 - Switch

16 x 10/100/1000 + 4 x Gigabit SFP - desktop - rack-mountable - AC 100/230 V

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1210-20/E
EAN/UPC	0790069467745



Description

D-Link Web Smart DGS-1210-20 - Switch - 16 x 10/100/1000 + 4 x Gigabit SFP - desktop, rack-mountable - AC 100/230 V

Main features

Product Description	D-Link Web Smart DGS-1210-20 - switch - 16 ports - rack-mountable
Device Type	Switch - 16 ports
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	16 x 10/100/1000 + 4 x Gigabit SFP
Performance	Switching capacity: 40 Gbps Forwarding performance (64-byte packet size): 29.8 Mpps
Capacity	IGMP groups: 256 Port queues: 4
MAC Address Table Size	16K entries
Routing Protocol	IGMP, IGMPv2
Remote Management Protocol	TFTP, Telnet, SNMP 1, SNMP 2c, SNMP 3, RMON 1, CLI, HTTP
Features	Auto-negotiation, flow control, full duplex mode, half duplex mode, auto-uplink (auto MDI/MDI-X), store and forward, 1MB packet buffer, Layer 2 switching, IGMP snooping, STP support, RSTP support, port mirroring, Multicast filtering function, LLDP support, QoS, WRR queuing, CoS, DSCP support, ToS, IPv6 support, bandwidth control, ACL support, IPv4 support, Port Security, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, Safeguard Engine, ARP support, DHCP snooping, 802.1x authentication, Cable Diagnostics Function, MIB, SNMP trap, TFTP support, BOOTP support, DHCP client, Syslog support, SNMP support, TFTP client, SNTP support, D-Link Green Technology
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.3ad (LACP), IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x
Power	AC 100/230 V (50/60 Hz)
Dimensions (WxDxH)	44 cm x 14 cm x 4.4 cm
Weight	2.2 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.