

D-Link Web Smart DGS-1210-28P

Switch - L3 - Managed - 24 x 10/100/1000 (PoE) + 4 x Gigabit SFP - desktop - rack-mountable - PoE (193 W)

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1210-28P/E
EAN/UPC	0790069467783



Description

D-Link Web Smart DGS-1210-28P - Switch - L3 - Managed - 24 x 10/100/1000 (PoE) + 4 x Gigabit SFP - desktop, rack-mountable - PoE (193 W)

Main features

Product Description	D-Link Web Smart DGS-1210-28P - switch - 24 ports - Managed - rack-mountable
Device Type	Switch - 24 ports - L3 - Managed
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE) + 4 x Gigabit SFP
Power Over Ethernet (PoE)	PoE
PoE Budget	193 W
Performance	Switching capacity: 56 Gbps Forwarding performance: 41.7 Mpps
Capacity	Layer 2 multicast addresses: 64 Virtual interfaces (VLANs): 256 ACL: 50
MAC Address Table Size	16K entries
Jumbo Frame Support	9216 bytes
Routing Protocol	IGMP, IGMPv2, MLD, MLDv2
Remote Management Protocol	SSH-2, SNMP 1, SNMP 2, SNMP 3, TFTP, RMON 1
Features	IGMP snooping, Loopback, LLDP support, STP support, RSTP support, flow control, port mirroring, Multicast filtering function, MDI/MDI-X switch, QoS, WRR queuing, DSCP support, ToS, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, Safeguard Engine, DHCP server, ARP inspection, DHCP snooping, 802.1x authentication, Port Security, DHCP client, MIB, SNTTP support, BOOTP support, system log, Cable Diagnostics Function, 3MB packet buffer
Compliant Standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3ad (LACP), IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1w, IEEE 802.3x, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x
Power	AC 120/230 V

Dimensions (WxDxH)	44 cm x 21 cm x 4.4 cm
--------------------	------------------------

Weight	2.54 kg
--------	---------

Technical data © 1WorldSync. Subject to technical modifications and errors.