

D-Link DGS 1510-28P - Switch - L3

smart - 24 x 10/100/1000 (PoE+) + 2 x Gigabit SFP + 2 x 10 Gigabit SFP+ - desktop - rack-mountable - PoE+ (193 W)

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1510-28P/E
EAN/UPC	0790069467936



Description

D-Link DGS 1510-28P - Switch - L3 - smart - 24 x 10/100/1000 (PoE+) + 2 x Gigabit SFP + 2 x 10 Gigabit SFP+ - desktop, rack-mountable - PoE+ (193 W)

Main features

Product Description	D-Link DGS 1510-28P - switch - 28 ports - smart - rack-mountable
Device Type	Switch - 28 ports - L3 - smart - stackable
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE+) + 2 x Gigabit SFP + 2 x 10 Gigabit SFP+
Power Over Ethernet (PoE)	PoE+
PoE Budget	193 W
Performance	Switching capacity: 92 Gbps Forwarding performance (64-byte packet size): 68.45 Mpps Stacking bandwidth: 40 Gbps
Capacity	Static MAC entries: 512 ARP entries: 256 IPv6 routes: 32 IPv4 routes: 64
MAC Address Table Size	16384 entries
Jumbo Frame Support	9216 bytes
Routing Protocol	IGMP, IGMPv2, IGMPv3, MLD, MLDv2, static IP routing
Remote Management Protocol	SNMP 1, SNMP 2c, SNMP 3, RMON 1, Telnet, CLI, TFTP, HTTP
Features	Auto-negotiation, full duplex capability, 1.5MB packet buffer, 2 fans, flow control, HOL Blocking Prevention, MSTP support, RSTP support, STP support, loopback detection, port mirroring, Multicast filtering function, Asymmetric VLAN, auto voice VLAN, MAC based VLAN, Protocol-based VLANs support, QoS, SPQ, DRR, WRR, ACL support, ARP spoofing, IPv4 support, IPv6 support, DoS attack prevention, Cable Diagnostics Function, LLDP support, LLDP-MED, auto-uplink (auto MDI/MDI-X)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3ae, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3ad (LACP), IEEE 802.1Q, IEEE

	802.1p, IEEE 802.3az, IEEE 802.1x
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	44 cm x 21 cm x 4.4 cm
Weight	2.54 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.