

D-Link DGS 1510-28XMP - Switch

L3 - smart - 24 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+ - desktop - rack-mountable - PoE+ (370 W)

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1510-28XMP/E
EAN/UPC	0790069467943



Description

D-Link DGS 1510-28XMP - Switch - L3 - smart - 24 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+ - desktop, rack-mountable - PoE+ (370 W)

Main features

Product Description	D-Link DGS 1510-28XMP - switch - 28 ports - smart - rack-mountable
Device Type	Switch - 28 ports - L3 - smart - stackable
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+
Power Over Ethernet (PoE)	PoE+
PoE Budget	370 W
Performance	Switching capacity: 128 Gbps Forwarding performance (64-byte packet size): 95.24 Mpps Stacking bandwidth: 40 Gbps
Capacity	Static MAC entries: 512 IGMP groups: 512 Layer 2 multicast addresses: 128 MLD groups: 512 ACL entries: 256 ACL rules: 768
MAC Address Table Size	16384 entries
Jumbo Frame Support	9216 bytes
Routing Protocol	IGMP, IGMPv2, IGMPv3, MLD, MLDv2
Remote Management Protocol	CLI, Telnet, TFTP, SNMP 1, SNMP 2c, SNMP 3, RMON 1, ICMP, HTTP
Features	Auto-negotiation, full duplex capability, 1.5MB packet buffer, 2 fans, flow control, HOL Blocking Prevention, STP support, MSTP support, RSTP support, loopback detection, port mirroring, Multicast filtering function, ERPS, QoS, SPQ, WRR, DRR, ACL support, Cable Diagnostics Function, sFlow, LLDP support, LLDP-MED, DHCP client, DHCP server, ARP spoofing, D-Link Green Technology, store and forward, auto-uplink (auto MDI/MDI-X), IGMP snooping, VLAN support, bandwidth control, MLD snooping, DAI, Broadcast Storm Control, Multicast Storm Control,

Unicast Storm Control, DoS attack prevention, DSCP support, WRR queuing, ARP support, D-Link SIM

Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3ad (LACP), IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3az
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	44 cm x 30.8 cm x 4.4 cm
Weight	4.25 kg
Localisation	Europe

Technical data © 1WorldSync. Subject to technical modifications and errors.