

D-Link DGS 1510-52X - Switch - L3

smart - 48 x 10/100/1000 + 4 x 10 Gigabit SFP+ - desktop - rack-mountable

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1510-52X/E
EAN/UPC	0790069467950



Description

D-Link DGS 1510-52X - Switch - L3 - smart - 48 x 10/100/1000 + 4 x 10 Gigabit SFP+ - desktop, rack-mountable

Main features

Product Description	D-Link DGS 1510-52X - switch - 52 ports - smart - rack-mountable
Device Type	Switch - 52 ports - L3 - smart - stackable
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	48 x 10/100/1000 + 4 x 10 Gigabit SFP+
Performance	Switching capacity: 176 Gbps Forwarding performance (64-byte packet size): 130.95 Mpps Stacking bandwidth: 40 Gbps
Capacity	Static MAC entries: 512 IPv6 routes (static): 32 IPv4 routes (static): 64 MLD groups: 512 IGMP groups: 512 Virtual interfaces (VLANs): 4094 Queues per port: 8 Static ARP entries: 256
MAC Address Table Size	16384 entries
Jumbo Frame Support	9216 bytes
Routing Protocol	IGMP, IGMPv2, IGMPv3, MLD, MLDv2, static IP routing
Remote Management Protocol	CLI, Telnet, TFTP, SNMP 1, SNMP 2c, SNMP 3, RMON 1, HTTP
Features	Flow control, full duplex mode, auto-uplink (auto MDI/MDI-X), store and forward, 3MB packet buffer, Smart Fan, auto-negotiation, ERPS, VLAN support, LLDP support, LLDP-MED, loopback detection, ACL support, Safeguard Engine, BPDU protection, anti-ARP spoofing, IPMB, DoS attack prevention, dual image support, D-Link Green Technology, EEE, IGMP snooping, MLD snooping, MSTP support, RSTP support, STP support, port mirroring, Multicast filtering function, QoS, SPQ, DRR, WRR, Cable Diagnostics Function, sFlow, DSCP based QoS, DHCP relay, NTP, ARP support, IPv6 support
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1s, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1x

Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	44 cm x 21 cm x 4.4 cm
Weight	3.1 kg
Localisation	Europe

Technical data © 1WorldSync. Subject to technical modifications and errors.