

D-Link SmartPro DGS-1530-28P - Switch

smart - 24 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+ - desktop - rack-mountable - PoE+ (370 W)

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DGS-1530-28P/E
EAN/UPC	0790069474590



Description

D-Link SmartPro DGS-1530-28P - Switch - smart - 24 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+ - desktop, rack-mountable - PoE+ (370 W)

Main features

Product Description	D-Link SmartPro DGS-1530-28P - switch - 28 ports - smart - rack-mountable
Device Type	Switch - 28 ports - smart - stackable
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+
Power Over Ethernet (PoE)	PoE+
PoE Budget	370 W
Performance	Switching capacity: 128 Gbps Forwarding performance: 95.24 Mpps Stacking bandwidth: 80 Gbps Packet buffer size: 1.5 MB
Capacity	VLAN groups: 4000 IPv6 routes: 32 IPv4 routes: 64 IPv4 interfaces: 64 IPv6 interfaces: 64 Queues per port: 8
MAC Address Table Size	16000 entries
Routing Protocol	Static IP routing, RSTP, MSTP
Remote Management Protocol	RSTP, SSH, SNMP, SNMP 3, SNMP 2c, CLI, OAM, RADIUS, RMON 1
Features	D-Link Green Technology, EEE, RSTP, MSTP support, Link Aggregation, Asymmetric VLAN, Auto Surveillance VLAN, auto voice VLAN, GVRP, IPv6 support, Protocol-based VLANs support, static route, ACL support, CoS, Egress ACL, Ingress ACL, 802.1x authentication, ARP spoofing, CLI management, IP-MAC binding, LLDP-MED, RADIUS support, 3 fans, LACP, Energy Efficient Ethernet, LLDP support, ARP support, reset button, flow control

Compliant Standards	IEEE 802.3az, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3ad (LACP), IEEE 802.1AX, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3at, IEEE 802.3af
Power	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH)	44 cm x 25 cm x 4.4 cm
Weight	3.8 kg
Localisation	Europe

Technical data © 1WorldSync. Subject to technical modifications and errors.