

D-Link DXS 1210-12TC - Switch

smart - 8 x 10GBase-T + 2 x combo 10 Gigabit SFP+/RJ-45 + 2 x SFP+ - desktop - rack-mountable

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	DXS-1210-12TC/E
EAN/UPC	0790069467653



Description

D-Link DXS 1210-12TC - Switch - smart - 8 x 10GBase-T + 2 x combo 10 Gigabit SFP+/RJ-45 + 2 x SFP+ - desktop, rack-mountable

Main features

Product Description	D-Link DXS 1210-12TC - switch - 12 ports - smart - rack-mountable
Device Type	Switch - 12 ports - smart
Enclosure Type	Rack-mountable
Subtype	10 Gigabit Ethernet
Ports	8 x 10GBase-T + 2 x combo 10 Gigabit SFP+/RJ-45 + 2 x SFP+
Performance	Switching capacity: 240 Gbps Forwarding performance: 178.56 Mpps
Capacity	VLAN groups: 4000 ACL rules: 256 Static ARP entries: 768 IPv4 routes (static): 64 IPv6 routes (static): 64 IGMP groups: 384 QoS hardware queues per port: 8 Packet buffer size: 2 MB
MAC Address Table Size	16K entries
Jumbo Frame Support	9KB
Routing Protocol	Static IPv4 routing, static IPv6 routing, IGMP, IGMPv2, IGMPv3, MLD, MLDv2
Remote Management Protocol	SNMP 1, SNMP 3, SNMP 2c, CLI, Telnet, HTTP, RMON 1, RMON 2, DHCP, TFTP, ICMP
Features	Auto-uplink (auto MDI/MDI-X), store and forward, LLDP support, LLDP-MED, flow control, MSTP support, RSTP support, STP support, loopback detection, Voice VLAN, GVRP, Asymmetric VLAN, CoS, QoS, DSCP based CoS, bandwidth control, DRR, WDRR, WRR, Broadcast Storm Control, Multicast Storm Control, Unicast Storm Control, DHCP server, DoS attack prevention, DAD, Cable Diagnostics Function, WAC, AAA, OTP, Guest VLAN, DHCP relay, DHCP client, dual image support, DNS client, D-Link Green Technology, BOOTP support, TFTP support, SNMP trap, port mirroring, IP-MAC binding, MLD snooping, SPQ, DWRR, ACL support, system log, DHCP snooping, ToS, DSCP

	support, HOL Blocking Prevention, ERPS, DAI, SNTP support, IP source guard, Safeguard Engine, IGMP snooping
Compliant Standards	IEEE 802.1p, IEEE 802.1Q, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3ae, IEEE 802.3az, IEEE 802.3z, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1x, IEEE 802.1D, IEEE 802.1s, IEEE 802.1w
Power	AC 100-240 V (50/60 Hz) 1.1 A
Dimensions (WxDxH)	44 cm x 21 cm x 4.4 cm
Weight	3.15 kg
Localisation	Europe

Technical data © 1WorldSync. Subject to technical modifications and errors.