

D-Link dlinkgo 8-Port Fast Ethernet Easy Desktop Switch GO-SW-8E

Switch - 8 x 10/100 - desktop

Group	Network Equipment
Manufacturer	D-Link
Manufacturer item no.	GO-SW-8E/E
EAN/UPC	0790069388286



Description

The dlinkgo GO-SW-8E 8-Port Fast Ethernet Easy Desktop Switch allows you to quickly set up a fast, reliable, and efficient wired network in your home or office. The GO-SW-8E is an unmanaged 10/100Mbps switch designed to enhance small workgroup performance while providing a high level of flexibility. Connect the GO-SW-8E to multiple computers to share files and folders, or connect it to a router to share an Internet connection.

Main features

Product Description	dlinkgo 8-Port Fast Ethernet Easy Desktop Switch GO-SW-8E - switch - 8 ports
Device Type	Switch - 8 ports
Subtype	Fast Ethernet
Ports	8 x 10/100
Performance	Switching capacity: 1.6 Gbps
MAC Address Table Size	2K entries
Jumbo Frame Support	2048 bytes
Features	Flow control, auto-sensing per device, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, half duplex mode, full duplex mode, fanless, Energy Efficient Ethernet
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
Dimensions (WxDxH)	14.15 cm x 7.85 cm x 2.38 cm

Extended details

General	
Device Type	Switch - 8 ports
Enclosure Type	Desktop
Subtype	Fast Ethernet
Ports	8 x 10/100
Performance	Switching capacity: 1.6 Gbps
MAC Address Table Size	2K entries
Jumbo Frame Support	2048 bytes

Features	Flow control, auto-sensing per device, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, half duplex mode, full duplex mode, fanless, Energy Efficient Ethernet
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
Status Indicators	Power, link/activity
	Expansion / Connectivity
Interfaces	8 x 100Base-TX RJ-45
	Power
Power Device	External power adapter
	Miscellaneous
MTBF	2,137,319 hours
Compliant Standards	FCC Class B certified, cUL, CB, RoHS, VCCI Class B
	Dimensions & Weight
Width	14.15 cm
Depth	7.85 cm
Height	2.38 cm
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-10 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.