Dell E2222H - LED monitor - 21.5" (21.45" viewable)

1920 x 1080 Full HD (1080p) @ 60 Hz - VA - 250 cd/m² - 3000:1 - 5 ms - VGA - DisplayPort - with 3 years Advanced Exchange Service - for OptiPlex 3090

Group	Flat Screens
Manufacturer	Dell
Manufacturer item no.	DELL-E2222H
EAN/UPC	5397184505342

Description

Dell E2222H - LED monitor - 21.5" (21.45" viewable) - 1920 x 1080 Full HD (1080p) @ 60 Hz - VA - 250 cd/m² - 3000:1 - 5 ms - VGA, DisplayPort - with 3 years Advanced Exchange Service - for OptiPlex 3090

Main features

Product Description	Dell E2222H - LED monitor - Full HD (1080p) - 21.5"
Device Type	LED-backlit LCD monitor - 21.5"
Energy Class	Class D
Power Consumption (On mode)	12.13 W
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.249 mm
Brightness	250 cd/m²
Contrast Ratio	3000:1
Response Time	10 ms (grey-to-grey normal); 5 ms (grey-to-grey fast)
Colour Support	16.7 million colours
Colour Gamut	72% (CIE 1931), 83% (CIE 1976)
Input Connectors	VGA, DisplayPort
Display Position Adjustments	Tilt
Screen Coating	Anti-glare 3H hardness
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - with stand	50.426 cm x 17.1 cm x 38.417 cm
Weight	3.04 kg
Environmental Standards	TCO Certified Displays 8, ENERGY STAR Qualified
Compliant Standards	RoHS, NFPA 99, BFR-reduced, PVC-reduced
Bundled Services	3 years Advanced Exchange Service

Designed For	OptiPlex 3090

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class D
Diagonal Size	21.5"
Viewable Size	21.45"
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.249 mm
Pixel Per Inch	103
Brightness	250 cd/m²
Contrast Ratio	3000:1
Colour Support	16.7 million colours
Colour Gamut	72% (CIE 1931), 83% (CIE 1976)
Response Time	10 ms (grey-to-grey normal); 5 ms (grey-to-grey fast)
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	30 - 83 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare 3H hardness
Backlight Technology	LED backlight
Features	LED edgelight system, Flicker Free technology, Mercury free, Dell ComfortView, arsenic free, Low Blue Light technology
Dimensions (WxDxH)	50.426 cm x 17.1 cm x 38.417 cm - with stand
Weight	3.04 kg
	Connectivity
Interfaces	VGA ¦ DisplayPort 1.2
	Mechanical
Display Position Adjustments	Tilt
Tilt Angle	-5/+21
	Miscellaneous
Features	Security lock slot (cable lock sold separately), VESA interface support
Cables Included	1 x DisplayPort cable
Compliant Standards	RoHS, NFPA 99, BFR-reduced, PVC-reduced
	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	12.13 W
Power Consumption SDR (On mode)	12.1 kWh/1000h
Power Consumption (Max)	19 Watt
Power Consumption Stand by	0.3 Watt

Power Consumption (Off Mode)	0.3 Watt
	Software / System Requirements
Included Software	Dell Display Manager
	Dimensions & Weight
Dimensions & Weight Details	With stand - width: 50.426 cm - depth: 17.1 cm - height: 38.417 cm - weight: 3.04 kg ¦ Without stand - width: 50.426 cm - depth: 4.964 cm - height: 29.538 cm - weight: 2.26 kg
	Dimensions & Weight (Shipping)
Shipping Weight	4.14 kg
	Environmental Standards
TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes
	Manufacturer Warranty
Bundled Services	3 years Advanced Exchange Service
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)
	Compatibility Information
Designed For	Dell OptiPlex 3090

Technical data © CNET Content Solutions. Subject to technical modifications and errors.