imcopex

Dell UltraSharp U2722D - LED monitor

27" - 2560 x 1440 QHD @ 60 Hz - IPS - 350 cd/m² - 1000:1 - 5 ms - HDMI - DisplayPort - with 3 years Advanced Exchange Service

Group	Flat Screens
Manufacturer	Dell
Manufacturer item no.	DELL-U2722D
EAN/UPC	5397184505007

Description

Elevated productivity. Vibrant color. Take your work to new heights with this 27-inch QHD monitor featuring wide color coverage, ComfortView Plus and fast connectivity.

Main features

Product Description	Dell UltraSharp U2722D - LED monitor - QHD - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class E
Power Consumption (On mode)	20 W
Features	USB 3.2 Gen 2/USB-C hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.2331 mm
Brightness	350 cd/m²
Contrast Ratio	1000:1
Response Time	8 ms (normal); 5 ms (fast)
Colour Support	1.07 billion colours
Input Connectors	HDMI, DisplayPort
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH) - with stand	61.134 cm x 18.5 cm x 38.513 cm
Environmental Standards	TCO Certified Displays 8, TCO Certified Edge Displays, ENERGY STAR Qualified
Compliant Standards	Plug and Play, RoHS, NFPA 99, TUV Rheinland, BFR-free, DisplayPort 1.4, HDCP 1.4, PVC-free
Bundled Services	3 years Advanced Exchange Service

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	27"
Built-in Devices	USB 3.2 Gen 2/USB-C hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.2331 mm
Pixel Per Inch	108.78
Brightness	350 cd/m²
Contrast Ratio	1000:1
Colour Support	1.07 billion colours
Response Time	8 ms (normal); 5 ms (fast)
Vertical Refresh Rate	49 - 76 Hz
Horizontal Refresh Rate	30 - 90 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	Picture by picture, 100% sRGB colour gamut, OSD lock, integrated cable management, Flicker Free technology, Mercury free, arsenic-free glass, 100% Rec 709 colour gamut, Dell Easy Arrange, Low Blue Light technology, Delta E<2 calibration, 95% DCI-P3
Dimensions (WxDxH)	61.134 cm x 18.5 cm x 38.513 cm - with stand
	Connectivity
Interfaces	HDMI ¦ DisplayPort 1.4 (HDCP 1.4) ¦ DisplayPort output ¦ USB-C 3.2 Gen 2 upstream ¦ USB-C 3.2 Gen 2 downstream (power up to 15W) ¦ 2 x USB 3.2 Gen 2 downstream ¦ USB 3.2 Gen 2 downstream with Battery Charging 1.2 ¦ Audio line-out (mini-jack)
	Mechanical
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	90
Rotation Angle	180
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately)
Cables Included	1 x DisplayPort cable - DisplayPort to DisplayPort - 1.8 m ¦ 1 x SuperSpeed USB cable - USB Type C to A - 1 m
Compliant Standards	Plug and Play, RoHS, NFPA 99, TUV Rheinland, BFR-free, DisplayPort 1.4, HDCP 1.4, PVC-free

Security Slot Type	Kensington security slot
	Power
Input Voltage	AC 120/230 V (50/60 Hz)
Power Consumption (On mode)	20 W
Power Consumption SDR (On mode)	20 kWh/1000h
Power Consumption (Typical)	20 Watt
Power Consumption (Max)	74 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.3 Watt
	Dimensions & Weight
Dimensions & Weight Details	With stand - width: 61.134 cm - depth: 18.5 cm - height: 38.513 cm ¦ Without stand - width: 61.134 cm - depth: 4.95 cm - height: 35.201 cm - weight: 4.38 kg
	Dimensions & Weight (Shipping)
Shipping Weight	9.62 kg
	Environmental Standards
TCO Certified	TCO Certified Displays 8, TCO Certified Edge Displays
ENERGY STAR Certified	Yes
	Manufacturer Warranty
Bundled Services	3 years Advanced Exchange Service
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.