

Dell UltraSharp U2723QE - LED monitor

27" - 3840 x 2160 4K @ 60 Hz - IPS - 400 cd/m² - 2000:1 - 5 ms - HDMI - DisplayPort - USB-C - with 3 years Advanced Exchange Service - Disti SNS

Group	Flat Screens
Manufacturer	Dell
Manufacturer item no.	DELL-U2723QE
EAN/UPC	5397184567753



Description

Dell UltraSharp U2723QE - LED monitor - 27" - 3840 x 2160 4K @ 60 Hz - IPS - 400 cd/m² - 2000:1 - 5 ms - HDMI, DisplayPort, USB-C - with 3 years Advanced Exchange Service - Disti SNS

Main features

Product Description	Dell UltraSharp U2723QE - LED monitor - 4K - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class F
Power Consumption (On mode)	25.9 W
Features	USB 3.2 Gen 2/USB-C hub, USB PD 90 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	4K 3840 x 2160 at 60 Hz
Pixel Pitch	0.1554 mm
Brightness	400 cd/m ²
Contrast Ratio	2000:1 / 2000:1 (dynamic)
Response Time	8 ms (grey-to-grey normal); 5 ms (grey-to-grey fast)
Colour Support	1.07 billion colours
Colour Gamut	100% Rec 709, 100% sRGB, 98% DCI-P3
Input Connectors	HDMI, DisplayPort, USB-C
Built-in Ethernet	Yes
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 100-240 V (50/60 Hz)

Dimensions (WxDxH) - with stand (lowest position)	61.14 cm x 18.5 cm x 38.518 cm
Weight	6.64 kg
Environmental Standards	ENERGY STAR Qualified EPEAT Gold
Compliant Standards	RoHS, BFR-free, PVC-free
Bundled Services	3 years Advanced Exchange Service - Disti SNS

Extended details

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class F
Energy Class (HDR)	Class G
Diagonal Size	27"
Built-in Devices	USB 3.2 Gen 2/USB-C hub
USB Power Delivery	90 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	4K 3840 x 2160 at 60 Hz
Pixel Pitch	0.1554 mm
Pixel Per Inch	163.18
Brightness	400 cd/m ²
Contrast Ratio	2000:1 / 2000:1 (dynamic)
Colour Support	1.07 billion colours
Colour Gamut	100% Rec 709, 100% sRGB, 98% DCI-P3
Response Time	8 ms (grey-to-grey normal); 5 ms (grey-to-grey fast)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	Mercury free, arsenic-free glass, Delta E<2 calibration, 3-sided bezeless
Dimensions (WxDxH)	61.14 cm x 18.5 cm x 38.518 cm - with stand (lowest position)
Weight	6.64 kg

Connectivity

Interfaces	HDMI (HDCP 2.2) DisplayPort 1.4 (HDCP 2.2) DisplayPort output USB-C upstream/DisplayPort 1.4 Alt Mode with Power Delivery (power up to 90W, HDCP 2.2) USB-C 3.2 Gen 2 upstream USB-C 3.2 Gen 2 downstream (power up to 15W) 4 x USB 3.2 Gen 2 downstream USB 3.2 Gen 2 downstream with Battery Charging 1.2 Audio line-out (mini-jack) LAN (RJ-45)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	60
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), VESA interface support, anti-theft protection
Cables Included	1 x USB-C to USB-C cable - 1 m 1 x DisplayPort cable - DisplayPort to DisplayPort - 1.8 m 1 x SuperSpeed USB cable - USB Type A to B
Compliant Standards	RoHS, BFR-free, PVC-free
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	25.9 W
Power Consumption SDR (On mode)	25.9 kWh/1000h
Power Consumption HDR (On mode)	37.7 kWh/1000h
Power Consumption (Max)	220 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.2 Watt
On / Off Switch	Yes
Dimensions & Weight	
Dimensions & Weight Details	With stand (lowest position) - width: 61.14 cm - depth: 18.5 cm - height: 38.518 cm - weight: 6.64 kg Without stand - width: 61.14 cm - depth: 5.433 cm - height: 35.301 cm - weight: 4.48 kg
Dimensions & Weight (Shipping)	
Shipping Weight	9.53 kg
Environmental Standards	
EPEAT Compliant	EPEAT Gold

ENERGY STAR
Certified

Yes

Manufacturer Warranty

Bundled Services

3 years Advanced Exchange Service - Disti SNS

Environmental Parameters

Min Operating
Temperature

0 °C

Max Operating
Temperature

35 °C

Humidity Range
Operating

10 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.