

# Eaton 9PX 3000i RT2U - UPS (rack-mountable / external)

AC 200/208/220/230/240 V - 3000 Watt - 3000 VA - 1-phase - RS-232 - USB - output connectors: 10 - PFC - 2U

Group	Power Supply
Manufacturer	Eaton
Manufacturer item no.	9PX3000IRT2U



## Description

The Eaton 9PX UPS provides energy-efficient power protection for small & medium Datacenters, IT rooms and Infrastructure. Delivering double conversion protection with 40% less energy usage and 28% more power 9PX is the perfect UPS for IT and Facility managers that are concerned by energy cost and are looking for next generation power protection solutions.

## Main features

Product Description	Eaton 9PX 3000i RT2U - UPS - 3000 Watt - 3000 VA
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Rack Size	2U
Weight	27.6 kg
Input Wiring	1-phase
Input Voltage	AC 200/208/220/230/240 V
Output Voltage	AC 200/208/220/230/240 V
Power Capacity	3000 Watt / 3000 VA
Input Connectors	1
Output connectors	8 x power IEC 60320 C13   2 x power IEC 60320 C19 16A
Networking	RS-232, USB
Dimensions (WxDxH)	44 cm x 60.5 cm x 8.65 cm
Environmental Standards	ENERGY STAR

## Extended details

### General

Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Height (Rack Units)	2U

### Power Device

UPS Technology	On-line
Input Voltage	AC 200/208/220/230/240 V
Input Voltage Range	AC 176 - 276 V
Input Wiring	1-phase

Frequency Required	40 - 70 Hz
Input Connectors	1
Power Output Connectors Details	8 x power IEC 60320 C13   2 x power IEC 60320 C19 16A
Output Voltage	AC 200/208/220/230/240 V
Power Capacity	3000 Watt / 3000 VA
Efficiency	98%
<b>Battery</b>	
Run Time (Up To)	60 min at 300 Watts   36 min at 500 Watts   23 min at 800 Watts   13 min at 1200 Watts   7 min at 1800 Watts   4 min at 2500 Watts
<b>Networking</b>	
Remote Management Interface	RS-232, USB
<b>Expansion / Connectivity</b>	
Interfaces	1 x management (USB)   1 x management (RS-232)
Expansion Slots	1 (total) / 1 (free) x Expansion Slot
<b>Miscellaneous</b>	
Features	LCD display, internal bypass
Compliant Standards	FCC Class B certified, TUV, CISPR 22 Class B, UL 1778, CB, IEC 62040-2, cULus, CSA 22.2, KC, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1
<b>Software / System Requirements</b>	
Software Included	Intelligent Power Software Suite
<b>Environmental Standards</b>	
ENERGY STAR	Yes
<b>Manufacturer Warranty</b>	
Service & Support	Limited warranty - 3 years   Limited warranty - batteries - 2 years
<b>Environmental Parameters</b>	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Sound Emission	40 dB
<b>Dimensions &amp; Weight</b>	
Width	44 cm
Depth	60.5 cm
Height	8.65 cm
Weight	27.6 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.