

Eaton 5SC 3000i R/T - UPS (rack-mountable / external)

AC 230 V - 2700 Watt - 3000 VA - RS-232 - USB - output connectors: 9 - 2U - black

Group	Power Supply
Manufacturer	Eaton
Manufacturer item no.	5SC3000IRT



Description

Eaton 5SC 3000VA Rack/Tower UPS provides line-interactive, affordable and reliable protection for small business servers. The 5SC includes an LCD interface for real-time status and measurements, and provides sinewave output for compatibility with today's most sensitive IT equipment. With its 8 IEC outputs and flexible design the 5SC fits anywhere easily.

Main features

Product Description	Eaton 5SC 3000i R/T - UPS - 2700 Watt - 3000 VA
Device Type	UPS - rack-mountable / external
Rack Size	2U
Weight	35.3 kg
Input Voltage	AC 230 V
Output Voltage	AC 220/230/240 V + 6% / - 10%
Power Capacity	2700 Watt / 3000 VA
Input Connectors	1 x power IEC 60320 C20 16A
Output connectors	8 x power IEC 60320 C13 1 x power IEC 60320 C19 16A
Run Time (Up To)	6 min at 70% load
Networking	RS-232, USB
Included Accessories	Rack mounting rails
Colour	Black
System Requirements	Apple MacOS, Linux, Microsoft Windows
Dimensions (WxDxH)	44.1 cm x 64.7 cm x 8.62 cm

Extended details

General

Device Type	UPS - rack-mountable / external
Height (Rack Units)	2U
Colour	Black

Power Device

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 184 - 276 V
Frequency Provided	50/60 Hz \pm 0.1%
Frequency Required	50/60 Hz
Input Connectors	1 x power IEC 60320 C20 16A
Power Output Connectors Details	8 x power IEC 60320 C13 1 x power IEC 60320 C19 16A
Output Voltage	AC 220/230/240 V + 6% / - 10% - 50/60 Hz
Power Capacity	2700 Watt / 3000 VA
Output Waveform	Sinewave
	Battery
Run Time (Up To)	10 min at half load 6 min at 70% load
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x management (USB) - 4 pin USB Type B 1 x management (RS-232) - 9 pin D-Sub (DB-9) 1 x remote power (on/off) - terminal block
Expansion Slots	1 Expansion Slot
	Miscellaneous
Included Accessories	Rack mounting rails
Rack Mounting Kit	Included
Features	Built-in 2 cooling fans, Advance Battery Management (ABM), LCD display, deep discharge protection, remote ON/OFF function, cooling fan, buck operation, booster technology, fader technology, high frequency line interactive technology
Compliant Standards	TUV, UL 1778, CB, IEC 62040-1-1, IEC 62040-2, cTUVus, EN 62040-1-1, EN 62040-2
	Software / System Requirements
Software Included	Eaton Intelligent Power Software Suite
OS Required	Apple MacOS, Linux, Microsoft Windows
	Manufacturer Warranty
Service & Support	Limited warranty - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Sound Emission	45 dB
	Dimensions & Weight
Width	44.1 cm
Depth	64.7 cm
Height	8.62 cm
Weight	35.3 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.