

Eaton 9SX 9SX3000I - UPS - AC 200/208/220/230/240 V

2700 Watt - 3000 VA - RS-232 - USB - output connectors: 9 - PFC

Group	Power Supply
Manufacturer	Eaton
Manufacturer item no.	9SX3000I



Description

The Eaton 9SX UPS offers high availability, flexibility and advanced protection for infrastructure, industrial, medical, IT, networking, storage and telecom. Delivering on-line double conversion protection in convenient tower, rack or RT format.

Main features

Product Description	Eaton 9SX 9SX3000I - UPS - 2700 Watt - 3000 VA
Device Type	UPS - Power Factor Correction (PFC) - external
Weight	33.4 kg
Input Voltage	AC 200/208/220/230/240 V
Output Voltage	AC 200/208/220/230/240 V
Power Capacity	2700 Watt / 3000 VA
Input Connectors	1 x power IEC 60320 C20 16A
Output connectors	8 x power IEC 60320 C13 10A ; 1 x power IEC 60320 C19 16A
Battery	Expandable
Networking	RS-232, USB
Dimensions (WxDxH)	21.4 cm x 41.2 cm x 34.6 cm

Extended details

	General
Device Type	UPS - Power Factor Correction (PFC) - external
	Power Device
UPS Technology	On-line
Input Voltage	AC 200/208/220/230/240 V
Input Voltage Range	AC 140 - 276 V
Frequency Provided	50/60 Hz
Frequency Required	40 - 70 Hz
Input Connectors	1 x power IEC 60320 C20 16A
Power Output Connectors Details	8 x power IEC 60320 C13 10A ; 1 x power IEC 60320 C19 16A

Output Voltage	AC 200/208/220/230/240 V 50/60 Hz
Power Capacity	2700 Watt / 3000 VA
Power Factor (PF)	0.9
Battery	
Type	Expandable
Run Time (Up To)	6 min at 2500 Watts
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (RS-232) - 9 pin D-Sub (DB-9) 1 x management (USB) - 4 pin USB Type B EPO (emergency power off) - mini terminal block Relay output - mini terminal block
Expansion Slots	1 (total) / 1 (free) x Expansion Slot
Miscellaneous	
Features	Advance Battery Management (ABM), LCD display, deep discharge protection, automatic self-test, temperature-compensated battery charging, 3-stage charging, double conversion, power measuring
Compliant Standards	FCC Class B certified, TUV, CISPR 22 Class B, UL 1778, CB, IEC 62040-3, CSA C22.2, IEC 62040-2, KCC, cULus, EN 62040-2, EAC, RCM, EN 62040-3, IEC 62040-1, EN 62040-1, BIS
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Sound Emission	45 dB
Dimensions & Weight	
Width	21.4 cm
Depth	41.2 cm
Height	34.6 cm
Weight	33.4 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.