

Elo Touch Solutions Elo 1093L - 90-Series - LED monitor

10.1" - open frame - touchscreen - 1280 x 800 @ 60 Hz - 350 cd/m²
- 800:1 - 25 ms - HDMI - VGA - DisplayPort - black

Group	Flat Screens
Manufacturer	Elo Touch Solutions
Manufacturer item no.	E321195
EAN/UPC	0815335025778



Description

The Elo 1093L 10.1-inch open-frame LCD touchscreen features a slim design and narrow outside dimensions thanks to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. This compact display is designed for touch, with proven Elo expertise and reliability built in. The 1093L provides stable, drift-free operation with outstanding image clarity and light transmission - for accurate touch responses and vivid images. Instantly grabbing and holding users' attention, the open-frame touchscreen is perfect for kiosks, casino and amusement, retail self-service, and industrial automation environments.

Main features

Product Description	Elo 1093L - 90-Series - LED monitor - 10.1"
Device Type	LED-backlit LCD monitor - 10.1" - touchscreen
Energy Class	Class A
Energy Consumption per Year	10 kWh
Power Consumption (On mode)	7 W
Features	Touch-screen
Aspect Ratio	16:10
Native Resolution	1280 x 800 at 60 Hz
Brightness	350 cd/m ²
Contrast Ratio	800:1
Response Time	25 ms (tr - tf)
Colour Support	262,000 colours
Input Connectors	HDMI, VGA, DisplayPort
Colour	Black
Dimensions (WxDxH)	25.58 cm x 3.69 cm x 17.85 cm
Weight	1.2 kg
Localisation	Worldwide
Compliant Standards	UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, IMERC

Extended details

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A
Energy Consumption per Year	10 kWh
Diagonal Size	10.1"
Aspect Ratio	16:10
Native Resolution	1280 x 800 at 60 Hz
Brightness	350 cd/m ²
Brightness w/touchscreen	315 cd/m ²
Contrast Ratio	800:1
Colour Support	262,000 colours
Response Time	25 ms (tr - tf)
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	30 - 60 kHz
Horizontal Viewing Angle	+85 / -85
Vertical Viewing Angle	+85 / -85
Backlight Technology	LED backlight
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	Remote OSD, Zero-Bezel Design, Projected Capacitive Touch (P-CAP) technology
Colour	Black
Dimensions (WxDxH)	25.58 cm x 3.69 cm x 17.85 cm
Weight	1.2 kg
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
Connectivity	
Interfaces	USB (Type B) VGA DisplayPort Management (RJ-45) HDMI
Mechanical	
VESA Mounting Interface	75 x 75 mm
Miscellaneous	
Cables Included	1 x VGA cable 1 x USB cable 1 x HDMI cable
Mounting Kit	Included
MTBF	50,000 hours
Compliant Standards	UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, IMERC
Localisation	Worldwide
Power	
Power Consumption (On mode)	7 W
Power Consumption Operational	6.1 Watt

Power Consumption (Typical)	6.1 Watt
Power Consumption Sleep	0.7 Watt
Power Consumption (Off Mode)	0.5 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.