

Elo Touch Solutions Elo ET1302L - With Stand - LCD monitor

13.3" - touchscreen - 1920 x 1080 Full HD (1080p) - 300 cd/m² - 800:1 - 25 ms - HDMI - VGA - USB-C - speakers - black

Group	Flat Screens
Manufacturer	Elo Touch Solutions
Manufacturer item no.	E683204
EAN/UPC	0843173109374



Description

The Elo 1302L 13-inch touchscreen monitor delivers a professional-grade interactive solution with Elo's industry-leading TouchPro PCAP technology featuring edge-to-edge glass and enabling up to 10 simultaneous touches. Backed by a three-year warranty, the feature rich touchscreen monitor is equipped with dual built-in speakers and USB Type C, VGA and HDMI video connectors. With a compact form factor, clean design aesthetic and flexible mounting options, The 1302L is well-suited for POS, self-service, signage and customer-facing point of interaction. Designed for commercial use, the new Elo touchscreen monitor makes business operations easy delivering energy efficiency and versatile accessories. The 1302L accessories include EMV, MSR, barcode scanner and customer facing display.

Main features

Product Description	Elo ET1302L - with Stand - LCD monitor - Full HD (1080p) - 13.3"
Device Type	LCD monitor - 13.3" - touchscreen
Energy Class	Class E
Power Consumption (On mode)	9 W
Features	Touch-screen
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080
Brightness	300 cd/m ²
Contrast Ratio	800:1
Response Time	25 ms
Colour Support	16.7 million colours
Input Connectors	HDMI, VGA, USB-C
Voltage	AC 120/230 V (50/60 Hz)
Colour	Black
Dimensions (WxDxH) - with stand	32.61 cm x 15 cm x 25.96 cm
Weight	2.32 kg
Compliant Standards	UL, VCCI, BSMI, cUL, NOM, CCC, IC, FCC, RoHS, KCC, WEEE, REACH, China RoHS, RCM

Extended details

General

Display Type	LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	13.3"
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080
Brightness	300 cd/m ²
Brightness w/touchscreen	270 cd/m ²
Contrast Ratio	800:1
Colour Support	16.7 million colours
Response Time	25 ms
Vertical Refresh Rate	60 Hz
Horizontal Refresh Rate	30 - 75 kHz
Horizontal Viewing Angle	+85 / -85
Vertical Viewing Angle	+85 / -85
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	Anti-glare, Projected Capacitive Touch (P-CAP) technology
Colour	Black
Dimensions (WxDxH)	32.61 cm x 15 cm x 25.96 cm - with stand
Weight	2.32 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	1 Watt
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
Connectivity	
Interfaces	VGA HDMI USB-C Headphone/microphone combo jack 4 x Micro-USB
Mechanical	
VESA Mounting Interface	75 x 75 mm
Miscellaneous	
Cables Included	HDMI cable USB-C to USB-A cable
Compliant Standards	UL, VCCI, BSMI, cUL, NOM, CCC, IC, FCC, RoHS, KCC, WEEE, REACH, China RoHS, RCM
Power	
Input Voltage	AC 120/230 V (50/60 Hz)
Power Consumption (On mode)	9 W
Power Consumption SDR (On mode)	9 kWh/1000h
Power Consumption (Typical)	9.8 Watt
Power Consumption Sleep	1.39 Watt

Power Consumption (Off Mode)	0.18 Watt
Dimensions & Weight (Shipping)	
Shipping Width	41.5 cm
Shipping Depth	22 cm
Shipping Height	33.3 cm
Shipping Weight	4.62 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.