

# Elo Touch Solutions Elo 1502L - M-Series - LED monitor

15.6" - touchscreen - 1920 x 1080 Full HD (1080p) @ 60 Hz - 300 cd/m<sup>2</sup> - 700:1 - 35 ms - HDMI - VGA - speakers - black

|                       |                     |
|-----------------------|---------------------|
| Group                 | Flat Screens        |
| Manufacturer          | Elo Touch Solutions |
| Manufacturer item no. | E155645             |
| EAN/UPC               | 0843173124575       |



## Description

The Elo 1502L 15.6-inch touchscreen monitor delivers a professional-grade interactive solution featuring Elo's industry-leading TouchPro PCAP technology with edge-to-edge glass enabling up to 10 simultaneous touches. The feature rich monitor offers a sleek, low-profile, commercial-ready solution with dual built-in speakers and USB Type B or C (depending on the model), VGA and HDMI video connectors. With a compact form factor and flexible mounting options, the 1502L is well-suited for POS, self-service, signage and customer-facing point of interaction. Designed for commercial use, the 1502L simplifies business operations by delivering energy efficiency and versatile accessory options - from EMV and MSR payment devices to a barcode scanner and customer facing display.

## Main features

|                                 |                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------|
| Product Description             | Elo 1502L - M-Series - LED monitor - Full HD (1080p) - 15.6"                                  |
| Device Type                     | LED-backlit LCD monitor - 15.6" - touchscreen                                                 |
| Features                        | Touch-screen                                                                                  |
| Aspect Ratio                    | 16:9                                                                                          |
| Native Resolution               | Full HD (1080p) 1920 x 1080 at 60 Hz                                                          |
| Brightness                      | 300 cd/m <sup>2</sup>                                                                         |
| Contrast Ratio                  | 700:1                                                                                         |
| Response Time                   | 35 ms                                                                                         |
| Colour Support                  | 16.7 million colours                                                                          |
| Input Connectors                | HDMI, VGA                                                                                     |
| Screen Coating                  | Anti-glare                                                                                    |
| Voltage                         | AC 120/230 V (50/60 Hz)                                                                       |
| Colour                          | Black                                                                                         |
| Dimensions (WxDxH) - with stand | 38.7 cm x 19.91 cm x 28.5 cm                                                                  |
| Weight                          | 3.05 kg                                                                                       |
| Compliant Standards             | UL, VCCI, BSMI, cUL, NOM, CB, CCC, IC, FCC, RoHS, KCC, WEEE, REACH, E-Standby, IPX1, RCM, BIS |

## Extended details

| General      |                                             |
|--------------|---------------------------------------------|
| Display Type | LED-backlit LCD monitor / TFT active matrix |

|                               |                                                                                                  |
|-------------------------------|--------------------------------------------------------------------------------------------------|
| Diagonal Size                 | 15.6"                                                                                            |
| Aspect Ratio                  | 16:9                                                                                             |
| Native Resolution             | Full HD (1080p) 1920 x 1080 at 60 Hz                                                             |
| Brightness                    | 300 cd/m <sup>2</sup>                                                                            |
| Brightness w/touchscreen      | 270 cd/m <sup>2</sup>                                                                            |
| Contrast Ratio                | 700:1                                                                                            |
| Colour Support                | 16.7 million colours                                                                             |
| Response Time                 | 35 ms                                                                                            |
| Vertical Refresh Rate         | 50 - 75 Hz                                                                                       |
| Horizontal Refresh Rate       | 31.5 - 82 kHz                                                                                    |
| Horizontal Viewing Angle      | +80 / -80                                                                                        |
| Vertical Viewing Angle        | +80 / -80                                                                                        |
| Screen Coating                | Anti-glare                                                                                       |
| Backlight Technology          | LED backlight                                                                                    |
| OSD Languages                 | Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese |
| Features                      | Edge-to-edge glass, Zero-Bezel Design, Projected Capacitive Touch (P-CAP) technology             |
| Colour                        | Black                                                                                            |
| Dimensions (WxDxH)            | 38.7 cm x 19.91 cm x 28.5 cm - with stand                                                        |
| Weight                        | 3.05 kg                                                                                          |
| <b>Audio</b>                  |                                                                                                  |
| Type                          | Speakers - stereo                                                                                |
| Output Power / Channel        | 2 Watt                                                                                           |
| <b>Input</b>                  |                                                                                                  |
| Type                          | Touch-screen - touchscreen                                                                       |
| Movement Detection Technology | Projected capacitive                                                                             |
| <b>Connectivity</b>           |                                                                                                  |
| Interfaces                    | Mini-VGA   HDMI   USB (Type C)   Audio line-in   3 x Micro-USB                                   |
| <b>Mechanical</b>             |                                                                                                  |
| VESA Mounting Interface       | 100 x 100 mm, 75 x 75 mm                                                                         |
| <b>Miscellaneous</b>          |                                                                                                  |
| Features                      | Security lock slot (cable lock sold separately), VESA interface support                          |
| Included Accessories          | 3 screws, 2 screws, cable clamp, 2 tie wraps                                                     |
| Cables Included               | 1 x HDMI cable   1 x USB-A to USB-C adapter                                                      |
| MTBF                          | 50,000 hour(s)                                                                                   |
| Compliant Standards           | UL, VCCI, BSMI, cUL, NOM, CB, CCC, IC, FCC, RoHS, KCC, WEEE, REACH, E-Standby, IPX1, RCM, BIS    |
| Security Slot Type            | Kensington security slot                                                                         |
| <b>Power</b>                  |                                                                                                  |

|                                           |                            |
|-------------------------------------------|----------------------------|
| Input Voltage                             | AC 120/230 V (50/60 Hz)    |
| Power Consumption (Typical)               | 12 Watt                    |
| Power Consumption Sleep                   | 2 Watt                     |
| Power Consumption (Off Mode)              | 0.2 Watt                   |
| <b>Dimensions &amp; Weight (Shipping)</b> |                            |
| Shipping Width                            | 20.4 cm                    |
| Shipping Depth                            | 45.1 cm                    |
| Shipping Height                           | 34.4 cm                    |
| Shipping Weight                           | 5.01 kg                    |
| <b>Manufacturer Warranty</b>              |                            |
| Service & Support                         | Limited warranty - 3 years |
| <b>Environmental Parameters</b>           |                            |
| Min Operating Temperature                 | 0 °C                       |
| Max Operating Temperature                 | 40 °C                      |
| Humidity Range Operating                  | 20 - 80% (non-condensing)  |

Technical data © 1WorldSync. Subject to technical modifications and errors.