

Elo Touch Solutions Elo 0702L - LED monitor - 7" - touchscreen

800 x 480 @ 60 Hz - 430 cd/m² - 500:1 - 25 ms - USB - black

Group	Flat Screens
Manufacturer	Elo Touch Solutions
Manufacturer item no.	E796382
EAN/UPC	0843173110721



Description

The Elo 0702L 7-inch touchscreen monitor delivers a professional-grade interactive solution with Elo's industry-leading TouchPro PCAP technology featuring edge-to-edge glass and enabling up to 10 simultaneous touches. The feature rich touchscreen monitor is equipped with DisplayLink technology - enabling connectivity for power, video and touch over a single cable. With a compact form factor measuring just over half an inch thin and a clean design made for simple integration, the 0702L is ideal for customer facing point of interaction installations in point-of-sale, brand loyalty, point of information, signage and hospitality applications. With a minimal footprint, the 0702L is also well-suited for industrial kitchen equipment controllers.

Main features

Product Description	Elo 0702L - LED monitor - 7"
Device Type	LED-backlit LCD monitor - 7" - touchscreen
Features	Touch-screen
Aspect Ratio	5:3
Native Resolution	800 x 480 at 60 Hz
Brightness	430 cd/m ²
Contrast Ratio	500:1
Response Time	25 ms
Colour Support	16.2 million colours
Input Connectors	USB
Voltage	DC 5 V
Colour	Black
Dimensions (WxDxH) - without stand	18.058 cm x 1.77 cm x 11.722 cm
Weight	350 g
Localisation	Worldwide
Compliant Standards	UL, VCCI, BSMI, cUL, NOM, CB, CCC, IC, FCC, KCC, IP65, RCM, IK06

Extended details

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	7"

Aspect Ratio	5:3
Native Resolution	800 x 480 at 60 Hz
Brightness	430 cd/m²
Contrast Ratio	500:1
Colour Support	16.2 million colours
Response Time	25 ms
Vertical Refresh Rate	60 Hz
Horizontal Refresh Rate	31.5 kHz
Horizontal Viewing Angle	150
Vertical Viewing Angle	120
Backlight Technology	LED backlight
Features	Anti-glare, USB bus powered, Projected Capacitive Touch (P-CAP) technology
Colour	Black
Dimensions (WxDxH)	18.058 cm x 1.77 cm x 11.722 cm - without stand
Weight	350 g
	Input
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
	Connectivity
Interfaces	Micro-USB
	Mechanical
VESA Mounting Interface	75 x 75 mm
	Miscellaneous
Cables Included	1 x USB cable
Compliant Standards	UL, VCCI, BSMI, cUL, NOM, CB, CCC, IC, FCC, KCC, IP65, RCM, IK06
Localisation	Worldwide
	Power
Input Voltage	DC 5 V
Power Consumption (Typical)	3.7 Watt
Power Consumption Sleep	0.9 Watt
Power Consumption (Off Mode)	1.9 Watt
	Dimensions & Weight (Shipping)
Shipping Width	23.2 cm
Shipping Depth	9.5 cm
Shipping Height	17 cm
Shipping Weight	650 g
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.