



Epson EH-TW9400 - 3LCD projector

3D - 2600 lumens (white) - 2600 lumens (colour) - Full HD (1920 x 1080) - 16:9
- 1080p - LAN - black

Group	Projectors
Manufacturer	Epson
Manufacturer item no.	V11H928040
EAN/UPC	8715946666303

Description

Enjoy the big screen experience at home with access to the 4K content with this affordable home cinema projector featuring sharp images, and an incredibly high contrast ratio, all with great connectivity and easy set up.

Main features

Product Description	Epson EH-TW9400 - 3LCD projector - 3D - LAN
Device Type	3LCD projector - 1080p
3D Capable	Yes (3D glasses sold separately)
Colour	Black
Brightness (White)	2600 lumens
Brightness (Colour)	2600 lumens
Contrast Ratio	1200000:1 (dynamic)
Resolution	Full HD (1920 x 1080)
Native Aspect Ratio	16:9
Colour Support	1.07 billion colours
Lens Shift Direction	Horizontal, vertical
Bulb type	UHE 250 Watt
Bulb life cycle	Up to 3500 hour(s) - normal mode Up to 5000 hour(s) - economic mode
Video Input	LAN
Power	AC 120/230 V (50/60 Hz)
Power Consumption Operational	355 Watt
Dimensions (WxDxH)	52 cm x 45 cm x 19.3 cm
Weight	11 kg

Extended details

General

Device Type	3LCD projector - 1080p
-------------	------------------------



3D Capable	Yes (3D glasses sold separately)
Networking	Gigabit Ethernet
Enclosure Colour	Black
Projector	
Brightness (White)	2600 lumens
Brightness (Colour)	2600 lumens
Contrast Ratio	1200000:1 (dynamic)
Image Size	127 cm - 762 cm
Projection Distance	3 m - 6.3 m
Throw Ratio	1.35 - 2.84:1
Resolution	Full HD - Full HD (1920 x 1080)
Native Aspect Ratio	16:9
Colour Support	1.07 billion colours
Max Sync Rate (V x H)	480 Hz
Bulb type	UHE 250 Watt
Bulb life cycle	Up to 3500 hour(s) - normal mode Up to 5000 hour(s) - economic mode
Features	Micro Lens Array (MLA) Technology, EPSON Super White, EPSON 3LCD technology, EPSON Cinema Filter, Control4 Certified, Crestron e-Control, Dynamic Mode, full 10-bit image processing, 10-position lens memory, AMX Control System, 4K Enhancement, Cinema Mode, RGB liquid crystal shutter, 3D depth adjustment, DCI colour gamut, frame interpolation, ISF certification, lens position memory, Super Resolution
Lens	
Focus Type	Powered
Lens Aperture	F/2.0-3.0
Zoom Type	Powered
Zoom Factor	2.1x
Keystone Correction Direction	Vertical
Vertical Keystone Correction	-30 / +30
Lens Shift Type	Powered
Lens Shift Direction	Horizontal, vertical
Vertical Lens Shift	96.3% / 96.3%
Horizontal Lens Shift	47.1% / 47.1%
Video Input	
Video Interfaces	VGA, HDMI
LAN and Wireless Image Transferring Protocols	Wired LAN
Expansion / Connectivity	
Interfaces	1 x USB 2.0 - 4 pin USB Type A 1 x USB 2.0 - 4 pin USB Type B (management) HDMI - 19 pin HDMI Type A 1 x network - RJ-45 1 x serial RS-232C - 9 pin D-Sub (DB-9) (management) 1 x VGA input 2 x HDMI input - 19 pin HDMI Type A
Miscellaneous	
Included Accessories	Wireless remote control, HDMI cable clamp
Security Features	Security lock slot (cable lock sold separately)



Security Slot Type	Kensington security slot
Power	
Power Source	AC
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Consumption Operational	355 Watt
Power Consumption Stand by	0.35 Watt
Software / System Requirements	
Software Included	EasyMP Multi PC Projection
Dimensions & Weight	
Width	52 cm
Depth	45 cm
Height	19.3 cm
Weight	11 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years - carry-in Limited warranty - lamp - 3 years / 3000 hours
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 90%
Sound Emission	24 dBA
Sound Emission (Economic Mode)	20 dBA

Technical data © CNET Content Solutions. Subject to technical modifications and errors.