



Epson EB-992F - 3LCD projector

4000 lumens (white) - 4000 lumens (colour) - Full HD (1920 x 1080) - 16:9 - 1080p - 802.11n wireless / LAN / Miracast - white

Group	Projectors
Manufacturer	Epson
Manufacturer item no.	V11H988040
EAN/UPC	8715946680781

Description

Maximize your presentations with this bright Full HD projector that's capable of producing a large and scalable screen size. The long-lasting lamp provides years of lessons before a replacement lamp is required or the air filter needs attention. It's easy to set up and offers a range of connectivity solutions, so you can quickly access content from multiple devices.

Main features

Product Description	Epson EB-992F - 3LCD projector - 802.11n wireless / LAN / Miracast - white
Device Type	3LCD projector - 1080p
Colour	White
Built-in Devices	Speaker
Brightness (White)	4000 lumens
Brightness (Colour)	4000 lumens
Contrast Ratio	16000:1 (dynamic)
Resolution	Full HD (1920 x 1080)
Native Aspect Ratio	16:9
Colour Support	1.07 billion colours
Bulb type	UHE 230 Watt
Bulb life cycle	Up to 6500 hour(s) - normal mode Up to 17000 hour(s) - economic mode
Video Input	IEEE 802.11n wireless / LAN / Miracast
Speakers	Speaker(s) - integrated
Power	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	327 Watt
Dimensions (WxDxH)	30.9 cm x 28.2 cm x 9 cm
Weight	3.1 kg

Extended details

General



Device Type	3LCD projector - 1080p
Built-in Devices	Speaker
Networking	802.11b/g/n, Ethernet
Enclosure Colour	White
Projector	
Brightness (White)	4000 lumens
Brightness (Colour)	4000 lumens
Brightness (Reduced)	2400 lumens
Contrast Ratio	16000:1 (dynamic)
Image Size	76 cm - 762 cm
Projection Distance	1.76 m - 2.86 m
Throw Ratio	1.32 - 2.14:1
Resolution	Full HD - Full HD (1920 x 1080)
Native Aspect Ratio	16:9
Colour Support	1.07 billion colours
Max Sync Rate (V x H)	120 Hz
Bulb type	UHE 230 Watt
Bulb life cycle	Up to 6500 hour(s) - normal mode † Up to 17000 hour(s) - economic mode
Features	Blackboard Mode, EPSON Quick Corner, Crystal Clear Fine (C2 Fine), Split Screen, PLink, Direct Power On, Direct Power Off, Control4 Certified, Dynamic Mode, USB Display, Extron Control System, AMX Control System, document camera compatible, Presentation Mode, Cinema Mode, RGB liquid crystal shutter
Lens	
Focus Type	Manual
Lens Aperture	F/1.51-1.99
Zoom Type	Manual
Zoom Factor	1.6x
Keystone Correction Direction	Horizontal, vertical
Vertical Keystone Correction	-30 / +30
Horizontal Keystone Correction	-30 / +30
Video Input	
Video Interfaces	VGA, HDMI, composite video
LAN and Wireless Image Transferring Protocols	IEEE 802.11b, IEEE 802.11g, wired LAN, IEEE 802.11n, Miracast
Speakers	
Type	Integrated
Sound Output Mode	Mono
Output Power / Channel	16 Watt
Speakers	1 x mixed channel
Expansion / Connectivity	
Interfaces	2 x VGA input - 15 pin HD D-Sub (HD-15) † 1 x VGA output - 15 pin HD D-Sub (HD-15) † 2 x HDMI input - 19 pin HDMI Type A † 1 x USB 2.0 - 4 pin USB Type A † 1 x USB 2.0 - 4 pin USB Type B † 2 x audio line-in - mini-phone stereo 3.5 mm † 1 x audio line-out - mini-phone stereo 3.5 mm † 1 x serial RS-232C - 9



pin D-Sub (DB-9) | 1 x network - RJ-45 | 1 x microphone | 1 x composite video input - RCA

Miscellaneous

Included Accessories	Wireless remote control, wireless LAN unit, battery for remote control
Cables Included	1 x VGA cable
Security Features	Security lock slot (cable lock sold separately), password protection, control panel lock, security cable hole
Security Slot Type	Kensington security slot

Power

Power Source	AC
Voltage Required	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	327 Watt

Dimensions & Weight

Width	30.9 cm
Depth	28.2 cm
Height	9 cm
Weight	3.1 kg

Manufacturer Warranty

Service & Support	Limited warranty - 5 years - carry-in Limited warranty - lamp - 5 years / 1000 hours
-------------------	--

Environmental Parameters

Min Operating Temperature	5 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80%
Sound Emission	37 dBA
Sound Emission (Economic Mode)	28 dBA

Technical data © CNET Content Solutions. Subject to technical modifications and errors.