

Epson WorkForce Enterprise WF-C20750 D4TW

Multifunction printer - colour - ink-jet - A3 (297 x 420 mm) - Ledger (279 x 432 mm) (original) - A3/Ledger (media) - up to 75 ppm (copying) - up to 75 ppm (printing) - 2350 sheets - 33.6 Kbps - Gigabit LAN - Wi-Fi(n) - NFC - USB 3.0 - USB 2.0 host

Group	Multifunction Printers
Manufacturer	Epson
Manufacturer item no.	C11CH87401
EAN/UPC	8715946677002



Description

This reliable, low-maintenance 4-in-1 device offers high-speed performance, superior image quality, all with significant sustainability advantages over laser models.

Main features

Product Description	Epson WorkForce Enterprise WF-C20750 D4TW - multifunction printer - colour
Device Type	Multifunction printer
Fax Type	Super G3 - plain paper
Printing Technology	Ink-jet (colour)
Inkjet Technology	Epson PrecisionCore - 4-ink
Monthly Duty Cycle (max)	400000 pages
Recommended Monthly Volume	8000 - 100000 pages
Max Copying Speed	Up to 75 ppm (mono) / up to 75 ppm (colour)
Max Copying Resolution	Up to 600 x 1200 dpi (mono) / up to 600 x 1200 dpi (colour)
Max Printing Speed	Up to 75 ppm (mono) / up to 75 ppm (colour)
Max Printing Resolution	Up to 600 x 2400 dpi (mono) / up to 600 x 2400 dpi (colour)
Max Fax Transmission Speed	33.6 Kbps
Scanning	600 x 600 dpi
Original Size	A3 (297 x 420 mm), Ledger (279 x 432 mm) (max)

Original Type	Sheets
Document Feeder Capacity	150 sheets
Media Size	55 x 127 mm (min) - 330 x 1200 mm (max)
Standard Media Capacity	2350 sheets
Max Media Capacity	5350 sheets
Bypass Feeder Capacity	150 sheets
Output Trays Capacity	550 sheets
Automatic Duplexing	Yes (copying) Yes (printing) Yes (scanning)
Connection Availability	Yes
Interface	Gigabit LAN, Wi-Fi(n), NFC, USB 3.0, USB 2.0 host
Office Machine Features	Scan to e-mail, scan to FTP, scan to PC, scan to USB host
Power	AC 100/240 V (50/60Hz)
Dimensions (WxDxH)	67.4 cm x 75.7 cm x 124.3 cm
Weight	177.1 kg

Extended details

	General
Device Type	Multifunction printer
Fax Type	Plain paper
Printing Technology	Ink-jet - colour
Monthly Duty Cycle (max)	400000 pages
Recommended Monthly Volume	8000 - 100000 pages
Display Colour Support	Colour
Display Features	Touch screen
Connection Availability	Yes
Interface	Gigabit LAN, Wi-Fi(n), NFC, USB 3.0, USB 2.0 host

Office Machine Features

Scan to e-mail, scan to FTP, scan to PC, scan to USB host

Copying

Max Copying Speed	Up to 75 ppm (mono) / up to 75 ppm (colour)
Max Copying Resolution	Up to 600 x 1200 dpi (mono) / up to 600 x 1200 dpi (colour)
Max Document Enlargement	400%
Max Document Reduction	25%
Maximum Copies	9999
Automatic Duplexing	Yes

Printing

Inkjet Technology	Epson PrecisionCore
Nozzle Configuration	8676 nozzles (black), 3 x 8676 nozzles (cyan, magenta, yellow)
Max Printing Resolution	Up to 600 x 2400 dpi (mono) / up to 600 x 2400 dpi (colour)
Max Printing Speed	Up to 75 ppm (mono) / up to 75 ppm (colour)
Ink Cartridge Configuration	5 cartridges (1 each: cyan, magenta, yellow; 2 black)
Ink Palette Supported (Colours)	Cyan, magenta, yellow, black
Colour	4-ink
Minimum Ink Droplet Size	3.5 pl
Printer Drivers / Emulations	PCL 6, PostScript 3, PCL 5c, EPSON ESC/P, PDF 1.7, EPSON ESC/P-R
Ink Type	Epson DURABrite Pro inks
Automatic Duplexing	Yes
First Print Out Time B/W	5.4 sec
First Print Out Time Colour	5.4 sec

Scanning

Scan Element	CIS
--------------	-----

Automatic Duplexing	Yes
Optical Resolution	600 x 600 dpi
	Fax Machine
Compatibility	Super G3
Max Transmission Speed	33.6 Kbps
Total Memory Capacity	Up to 550 pages
	Fax Machine Features
Error Correction Mode (ECM)	Yes
Speed Dialing	2000 station(s)
Features	Automatic redialing, delayed sending
	Document & Media Handling
Max Original Size	A3 (297 x 420 mm), Ledger (279 x 432 mm)
Original Type	Sheets
Document Feeder Capacity	150 sheets
Min Media Size	55 x 127 mm
Max Media Size	A3/Ledger
Min Media Weight	60 g/m ²
Max Media Weight	350 g/m ²
Supported Media Sizes	Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), A3 (297 x 420 mm), B4 (250 x 353 mm), A6 (105 x 148 mm), ANSI B (Ledger) (279 x 432 mm), SRA3 (320 x 450 mm), B6 (125 x 176 mm), A3 Plus (329 x 483 mm)
Supported Envelope Sizes	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C6 (114 x 162 mm), International C5 (162 x 229 mm), International C4 (229 x 324 mm)
Standard Media Capacity	2350 sheets
Max Media Capacity	5350 sheets
Bypass Feeder Capacity	150 sheets
Output Trays Capacity	550 sheets

Document & Media Handling Details	ADF - 150 sheets Input tray - 150 sheets size: 55 x 127 mm - 330 x 1200 mm weight: 60 g/m ² - 350 g/m ² 4 x input tray - 550 sheets - A3 (297 x 420 mm) weight: 60 g/m ² - 160 g/m ² Output tray - 550 sheets
Speed Details	Printing: up to 75 ppm - B/W (ISO/IEC 24734) Printing: up to 75 ppm - colour (ISO/IEC 24734) Printing: up to 75 ppm (A4) - B/W duplex (ISO/IEC 24734) Printing: up to 75 ppm (A4) - colour duplex (ISO/IEC 24734) Printing: up to 45 ppm (A3) - B/W (ISO/IEC 24734) Printing: up to 45 ppm (A3) - colour (ISO/IEC 24734) Copying: up to 75 ipm - B/W (ISO/IEC 24735) Scanning: up to 110 ipm (A4) - B/W duplex Scanning: up to 60 ipm (A4) - colour Scanning: up to 110 ipm (A4) - colour duplex Copying: up to 75 ipm - colour (ISO/IEC 24735)
	Connections
Interfaces	1 x USB 3.0 1 x USB 2.0 host - 4 pin USB Type A 1 x Gigabit LAN - RJ-45
Security Protocols & Features	LDAP, SSL, WEP, TLS, IPsec, 802.1x, WPA2-PSK, PING, Wi-Fi Direct, WPA2-Enterprise
Operating System Support	MS Windows XP SP2 or later, MS Windows XP Professional x64 Edition, MS Windows 7, MS Windows Vista, MS Windows Server 2008 R2, Apple Mac OS X 10.7.x, MS Windows Server 2003 R2, Apple Mac OS X 10.8.x, Windows 8, Apple Mac OS X 10.6.8, Windows 8.1, MS Windows Server 2012 R2, Apple Mac OS X 10.9.x, Windows 10, Apple Mac OS X 10.10.x, Apple Mac OS X 10.11.x
	Power
Voltage Required	AC 100/240 V (50/60Hz)
Power Consumption Operational	160 Watt
Power Consumption Standby	76 Watt
Power Consumption Sleep	1.1 Watt
	Miscellaneous
Compliant Standards	CISPR 22 Class B, FCC Part 15 B, UL 60950-1, CAN/CSA-C22.2 No. 60950-1
	Dimensions & Weight
Width	67.4 cm
Depth	75.7 cm
Height	124.3 cm
Weight	177.1 kg
	Environmental Parameters
Sound Emission	60 dBA (operating)
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C

Humidity
Range
Operating

15 - 85% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.