Fujitsu B2410 WE - LED monitor

24.1" - 1920 x 1200 WUXGA - IPS - 300 cd/m² - 1000:1 - 5 ms - HDMI - DVI-D - VGA - DisplayPort - speakers - marble grey

Group	Flat Screens
Manufacturer	Fujitsu
Manufacturer item no.	S26361-K1697-V140
EAN/UPC	4065221160205

Description

The Fujitsu Display B2410 WE combines picture-performance and ergonomics in daily office life. It comes in a user-optimized design, as Fujitsu innovated the display housing by offering the worldwide first right-hand USB hub that ensures an optimal cable course. This makes it ergonomically perfect for most users.
The factory pre-calibrated display provides high color fidelity for single and multimonitor usage. Retina protection by low blue light panel that culls damaging blue light without any loss or changes of color.
The integrated Autobrightness sensor adapts the brightness of the display to an optimum, saves energy and increases constant productivity due to reduced eye strain.
The integrated presence sensor increases the protection of personal data, activating Windows password lock by temporary user's absence. Its holistic portfolio of interfaces consisting of modern digital (Display Port and HDMI) plus legacy interfaces like DVI and VGA, makes the monitor being universally applicable.

Main features

Product Description	Fujitsu B2410 WE - LED monitor - 24.1"
Device Type	LED-backlit LCD monitor - 24.1"
Energy Class	Class C
Energy Consumption per Year	43.92 kWh
Features	Presence sensor, USB 3.2 Gen 1 hub
Panel Type	IPS
Aspect Ratio	16:10
Native Resolution	WUXGA 1920 x 1200
Pixel Pitch	0.27 mm
Brightness	300 cd/m²
Contrast Ratio	1000:1 / 20000000:1 (dynamic)
Response Time	5 ms
Colour Support	16.7 million colours
Colour Gamut	77% NTSC, 99% sRGB
Input Connectors	HDMI, DVI-D, VGA, DisplayPort
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating

Voltage	AC 100-240 V (50/60 Hz)
Colour	Marble grey
Dimensions (WxDxH) - with stand	53.22 cm x 21.27 cm x 36.573 cm
Weight	6.14 kg
Localisation	Europe
Environmental Standards	TCO Certified Displays 8, ENERGY STAR Qualified EPEAT Silver
Compliant Standards	FCC Class B certified, TUV GS, RoHS, WEEE, S Mark, cTUVus, Directive 2004/108/EEC, EAC, TUV Rheinland Low Blue Light Certification, TUV Rheinland Flicker Free Certification, EN 62368-1, ISO 9241-307 Class 1

Extended details

	General
Display Type	LED-backlit LCD monitor
Energy Class	Class C
Energy Consumption per Year	43.92 kWh
Diagonal Size	24.1"
Built-in Devices	Presence sensor, USB 3.2 Gen 1 hub
Panel Type	IPS
Aspect Ratio	16:10
Native Resolution	WUXGA 1920 x 1200
Pixel Pitch	0.27 mm
Brightness	300 cd/m²
Contrast Ratio	1000:1 / 20000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	77% NTSC, 99% sRGB
Response Time	5 ms
Vertical Refresh Rate	48 - 76 Hz
Horizontal Refresh Rate	30 - 82 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Colour Temperature	5000K, 6500K, 7500K
OSD Languages	Danish, Czech, Chinese (traditional), Chinese (simplified), English, German, French, Italian, Norwegian, Portuguese, Polish, Finnish, Swedish, Russian, Spanish, Dutch, Turkish, Arabic, Japanese

Features	Eco-Mode, Auto Brightness Control, ECO button, DisplayView, Workplace Lighting Guide, 24/7 operating mode
Colour	Marble grey
Dimensions (WxDxH)	53.22 cm x 21.27 cm x 36.573 cm - with stand
Weight	6.14 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Connectivity
Interfaces	DisplayPort 1.2 ¦ DVI-D (HDCP) ¦ HDMI ¦ VGA ¦ Headphones ¦ Audio line-in ¦ 3 x USB 3.2 downstream (Type A) ¦ USB 3.2 downstream (Type C) ¦ USB 3.2 Gen 1 upstream (Type B)
	Mechanical
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+35
Swivel Angle	345
Rotation Angle	90
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately)
Cables Included	1 x DisplayPort cable - 1.8 m ¦ USB cable - USB Type A to B - 1.8 m
Compliant Standards	FCC Class B certified, TUV GS, RoHS, WEEE, S Mark, cTUVus, Directive 2004/108/EEC, EAC, TUV Rheinland Low Blue Light Certification, TUV Rheinland Flicker Free Certification, EN 62368-1, ISO 9241-307 Class 1
Localisation	Europe
Security Slot Type	Kensington security slot
	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	12.4 kWh/1000h
Power Consumption (Max)	24.8 Watt
Power Consumption Stand by	0.38 Watt
Power Consumption Sleep	0.1 Watt
	Dimensions & Weight
Dimensions & Weight Details	With stand - width: 53.22 cm - depth: 21.27 cm - height: 36.573 cm - weight: 6.14 kg ¦ Without stand - width: 53.22 cm - depth: 5.921 cm - height: 35.07 cm - weight: 4.24 kg
	Dimensions & Weight (Shipping)

Shipping Width	16.2 cm
Shipping Depth	73.4 cm
Shipping Height	45 cm
Shipping Weight	8.79 kg
	Environmental Standards
TCO Certified	TCO Certified Displays 8
EPEAT Compliant	EPEAT Silver
ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 85% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.