imcopex

Fujitsu USB 3.0 Port Replicator PR08

Docking station - USB - GigE - for ESPRIMO D538/E94 - P558 - Q958; LIFEBOOK E5410 - E5510 - U7310 - U7410 - U7510 - U9310

Group	USB hubs
Manufacturer	Fujitsu
Manufacturer item no.	S26391-F6007-L400
EAN/UPC	4051554306229

Description

The Fujitsu USB 3.0 port replicator PR08 is the solution for notebooks without a dedicated docking connector or in hot-desk environments. You can connect to the local area network, and to all of your peripherals with a single USB 3.0 plug and boost your productivity by extending your workspace over up to four displays.

Main features

Product Description	Fujitsu USB 3.0 Port Replicator PR08 - docking station - USB - GigE
Product Type	Docking station
Docking Interface	USB
Dimensions (WxDxH)	4 cm x 7.8 cm x 19 cm
Weight	350 g
Colour	Black, marble grey
Localisation	Australia, China, New Zealand, United Kingdom, United States, Europe
Networking	Gigabit Ethernet
Power	Power adapter - external AC 120/230 V (50/60 Hz)
Designed For	Celsius J580; ESPRIMO D538/E94, D556, D738/E94, D757, D757/E94, D956, D957, D957/E94, D958, D958/E94, E420, E720, P556, P558, P720, P756, P756 E94, P920, P956/E94, P957, Q520, Q920, Q956, Q958; LIFEBOOK E5410, E5510, E734, E744, E754, S935, T725, U7310, U7410, U745, U7510, U9310; Stylistic Q704

Extended details

	General
Product Type	Docking station
Width	4 cm
Depth	7.8 cm
Height	19 cm
Weight	350 g

Enclosure Colour	Black, marble grey
Localisation	Australia, China, New Zealand, United Kingdom, United States, Europe
	Networking
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
	Expansion / Connectivity
Interfaces	1 x audio - line-in/microphone - mini-phone stereo 3.5 mm ¦ 1 x audio - line-out/headphones - mini-phone stereo 3.5 mm ¦ 1 x SuperSpeed USB 3.0 - 9 pin USB Type B ¦ 2 x USB 2.0 - 4 pin USB Type A ¦ 2 x SuperSpeed USB 3.0 - 9 pin USB Type A ¦ 1 x audio / video - DisplayPort - 20 pin DisplayPort ¦ 1 x display / video - DVI-Analog/Digital - 24+5 pin combined DVI ¦ 1 x network - 10Base-T/100Base-TX/1000Base-T - RJ-45
	Miscellaneous
Cables Included	1 x DVI-VGA adapter - external ¦ 1 x SuperSpeed USB cable - external - 1 m
Features	Security lock slot (cable lock sold separately), LED indicator, DisplayLink DL-3900 chipset
Compliant Standards	FCC Class B certified, VCCI, C-Tick, BSMI, NOM, ICES-003 Class B, CCC, EK, PSE Mark, cULus, MEPS, KC
	Power
Power Device	Power adapter - external
Voltage Required	AC 120/230 V (50/60 Hz)
	Environmental Parameters
Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
	Compatibility Information
Designed For	Fujitsu Celsius J580, M720, M720 POWER, M720 PREMIUM selection, M720 proGREEN selection, M740, R920, R920 PREMIUM selection, W420, W420 proGREEN selection, W520, W520 POWER, W520 proGREEN selection ¦ Fujitsu CELSIUS Mobile H720 ¦ Fujitsu ESPRIMO C710, C910-L, D538/E94+, D556/2/E85+, D556/2/E90+, D556/E85+, D556/E90+, D556/PX, D738/E94+, D757/E85+, D757/E90+, D757/E94+, D956/M (International Energy Star Program), D957/E85+, D957/E90+, D957/E94+, D958/E85+, D958/E94+, E400 E85+, E420 E85+, E720 E85+, E720 E90+, E920 0-Watt, E920 E85+, E920 E90+, P420 E85+, P556 E85+, P556 E90+, P556/2/E85+, P558, P720 E85+, P720 E90+, P756 E85+, P756 E90+, P756 E94+, P920 0-Watt, P920 E85+, P920 E90+, P956/E94+, P957/power, Q520, Q520/K, Q910, Q910 PREMIUM, Q920, Q956/MRE, Q958/MRE ¦ Fujitsu ESPRIMO Mobile D9510, M9410, M9415, U9210, U9215, V5505, V5545, V6505, V6535, V6545, X9510, X9515, X9515 proGREEN, X9525 ¦ Fujitsu LIFEBOOK A514, A532, A555, E5410, E544, E5510, E554, E734, E744, E754, LH531, LH532, P3110, P8110, S935, SH531, T580, T725, T935, U7310, U7410, U745, U7510, U904, U9310, U9310x ¦ Fujitsu Stylistic Q550, Q584, Q704

Technical data © CNET Content Solutions. Subject to technical modifications and errors.