



HP 651A Cyn Contract LJ Toner Cartridge, 16000 pages, Cyan, 1 pc(s)

651A Cyan Original LaserJet Toner Cartridge

Group	Toner Cartridges
Manufacturer	HP
Manufacturer item no.	CE341AC
EAN/UPC	0886111124954

Description

Ideal for enterprise workgroups with managed printing environments and small- and medium-size businesses that are do-it-yourself marketers.

HP 651A Cyan LaserJet Toner Cartridge produces standout business documents with glossy, photo-like colour. Keep business productivity high and avoid wasted time and supplies with reliable Original HP toner cartridges.

- Produce standout business documents and marketing materials, using Original HP Toner Cartridges with HP ColorSphere technology. Get consistent, print shop-quality results on a wide range of laser papers designed for professional office printing.
- Keep printing costs low while maintaining productivity. Original HP Color LaserJet Toner Cartridges deliver consistent, uninterrupted printing. Avoid wasted supplies and expensive delays with cartridges that are designed for exceptional reliability.
- Track cartridge use and reorder easily with intelligence built into Original HP toner cartridges. Automatic seal removal makes installation quick and easy. Enjoy easy recycling – cartridges returned via HP Planet Partners are recycled responsibly.^[2]

Main features

General

Quantity per pack	1 pc(s)
Colour toner page yield	16000 pages
Printing colours	Cyan

Extended details

Other features

Page yield footnote	ISO/IEC 19798
Product colour	Black

Weight & dimensions

Package depth	188 mm
Package type	Box
Package height	225 mm
Package width	492 mm
Package weight	2.72 kg

Features

Quantity per pack	1 pc(s)
Colour toner page yield	16000 pages
Printing colours	Cyan
Type	Original
Print technology	Laser printing
OEM code	CE341AC
Compatibility	HP LaserJet Enterprise M775
Brand compatibility	HP
Cartridge capacity	Standard Yield

Operational conditions

Storage relative humidity (H-H)	10 - 80 %
Storage temperature (T-T)	-20 - 40 °C
Operating temperature (T-T)	10 - 40 °C
Operating relative humidity (H-H)	20 - 80 %