



HP 653X Blk Contract LJ Toner Cartridge, 20000 pages, Black, 1 pc(s)

653X High Yield Black Original LaserJet Toner Cartridge

Group	Toner Cartridges
Manufacturer	HP
Manufacturer item no.	CF320XC
EAN/UPC	0888182056868

Description

Ideal for enterprise workgroups with managed printing environments, and small and medium-size businesses that carry out in-house marketing.

HP 653 LaserJet Printing Supplies produce standout business documents with glossy, photo-quality colour. HP ColorSphere technology delivers consistent, professional colour. Avoid wasted time and supplies with reliable Original HP toner cartridges.

- Produce standout business documents and marketing materials using Original HP toner cartridges with HP ColorSphere technology. Get consistent, print shop-quality results on a wide range of papers designed for professional office printing.
- Count on trustworthy printing supplies to maintain productivity. HP LaserJet toner cartridges deliver consistent, uninterrupted printing. Because cartridges are designed for exceptional reliability, you avoid wasted supplies and expensive delays.
- Track cartridge use and reorder easily with intelligence built into Original HP toner cartridges. Automatic seal removal makes installation quick and easy.
- Use Original HP toner cartridges to help save energy and resources. Enjoy easy recycling – cartridges returned through HP Planet Partners are recycled responsibly^[1].

Main features

General	
Quantity per pack	1 pc(s)
Printing colours	Black
Black toner page yield	20000 pages

Extended details

Weight & dimensions



Package depth	164 mm
Package type	Box
Depth	164 mm
Weight	1.3 kg
Package height	214 mm
Package width	390 mm
Package weight	1.84 kg
Height	214 mm
Width	390 mm

Features

Quantity per pack	1 pc(s)
Printing colours	Black
Black toner page yield	20000 pages
Type	Original
Print technology	Laser printing
OEM code	CF320XC
Compatibility	HP Color LaserJet Enterprise M680
Brand compatibility	HP
Cartridge capacity	High (XL) Yield

Operational conditions

Storage temperature (T-T)	-20 - 40 °C
Operating temperature (T-T)	15 - 27 °C
Operating relative humidity (H-H)	10 - 70 %