



HP CE285AC Blk Contract LJ Toner Crtg, 1600 pages, Black, 1 pc(s)

85A Black Original LaserJet Toner Cartridge

Group	Toner Cartridges
Manufacturer	HP
Manufacturer item no.	CE285AC
EAN/UPC	0887758522554

Description

Ideal for small businesses and home office users who have limited budgets, space and IT support, and who want to print everyday business documents easily.

Get a great value for everyday business printing. HP LaserJet toner cartridges help you print professional quality reports, letters and invoices with ease.

- Get a great value for all your everyday business printing needs. Legendary HP reliability can save you time, minimise downtime and deliver professional results you can count on.
- Produce bold, crisp text and sharp black-and-white images. Use HP LaserJet printers together with Original HP toner cartridges to achieve consistent, professional results.
- This all-in-one HP LaserJet print cartridge makes replacing a print cartridge quick and easy. And get reliable, easy-to-use printing and supplies management, plus convenient, free recycling.

Main features

General

Quantity per pack	1 pc(s)
Printing colours	Black
Black toner page yield	1600 pages

Extended details

Weight & dimensions

Package depth	113 mm
Package type	Box
Weight	620 g
Package height	125 mm
Package width	375 mm
Package weight	830 g

Logistics data

Pallet weight	214.7 kg
Quantity per EUR-pallet	168 pc(s)
Number of cartons per pallet	234
Number of cartons per pallet layer	26
Number of cartons per EUR-pallet layer	21
Pallet height	126.9 cm
Pallet width	117.5 cm
Pallet length	100 cm
EUR-pallet weight	159.9 kg
Number of layers per pallet	9
Quantity per pallet	234 pc(s)

Features

Quantity per pack	1 pc(s)
Printing colours	Black
Black toner page yield	1600 pages
Type	Original
Country of origin	Japan
Print technology	Laser printing
OEM code	CE285AC
Compatibility	HP LaserJet Pro M1132/M1212/M1217/P1102
Brand compatibility	HP
Cartridge capacity	Standard Yield

Operational conditions

Storage relative humidity (H-H)	10 - 90 %
Storage temperature (T-T)	-20 - 40 °C
Operating temperature (T-T)	10 - 32.5 °C
Operating relative humidity (H-H)	20 - 80 %