



HP Color LaserJet Pro MFP M479fdw

Multifunction printer - colour - laser - Legal (216 x 356 mm) (original) - A4/Legal (media) - up to 27 ppm (copying) - up to 27 ppm (printing) - 300 sheets - 33.6 Kbps - USB 2.0 - LAN - Wi-Fi(n) - USB host

Group	Multifunction Printers
Manufacturer	HP
Manufacturer item no.	W1A80A#B19
EAN/UPC	0192018996892

Description

Winning in business means working smarter. The HP Color LaserJet Pro MFP M479 is designed to let you focus your time where it's more effective - growing your business and staying ahead of the competition.

Main features

Product Description	HP Color LaserJet Pro MFP M479fdw - multifunction printer - colour
Device Type	Multifunction printer
Fax Type	Plain paper
Localisation	English, German, French, Italian, Spanish / Europe
Printing Technology	Laser (colour)
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	750 - 4000 pages
Max Copying Speed	Up to 27 ppm (mono) / up to 27 ppm (colour)
Max Copying Resolution	Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (colour)
Max Printing Speed	Up to 27 ppm (mono) / up to 27 ppm (colour)
Max Printing Resolution	Up to 38400 x 600 dpi (mono) / up to 38400 x 600 dpi (colour)
Max Fax Transmission Speed	33.6 Kbps
Fax Resolutions	203 x 196 dpi, 300 x 300 dpi, 203 x 96 dpi
Scanning	1200 x 1200 dpi
Display	4.3"
Original Size	102 x 152 mm (min) - Legal (216 x 356 mm) (max)
Original Type	Sheets
Document Feeder Capacity	50 sheets
Media Size	76 x 127 mm (min) - Legal (216 x 356 mm), A4 (210 x 297 mm) (max)
Media Type	Transparencies, envelopes, plain paper, cards, labels, recycled paper, photo paper, bond paper, glossy paper
Standard Media Capacity	300 sheets
Max Media Capacity	850 sheets



Bypass Feeder Capacity	50 sheets
Output Trays Capacity	150 sheets
Automatic Duplexing	Yes (copying) Yes (printing) Yes (scanning)
Connection Availability	Yes
Interface	USB 2.0, LAN, Wi-Fi(n), USB host
AirPrint Enabled	Yes
Office Machine Features	Print from USB flash drive, save to USB flash drive, scan to e-mail, scan to folder, scan to network, scan to Cloud
Power	AC 220 V (50/60Hz)
Dimensions (WxDxH)	41.6 cm x 47.2 cm x 40 cm
Weight	23.4 kg
Environmental Standards	ENERGY STAR Qualified, Blue Angel

Extended details

General	
Printer Fonts	TrueType x 84
Device Type	Multifunction printer
Fax Type	Plain paper
Printing Technology	Laser - colour
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	750 - 4000 pages
Display Diagonal Size	4.3"
Display Colour Support	Colour
Display Features	Touch screen
Connection Availability	Yes
Interface	USB 2.0, LAN, Wi-Fi(n), USB host
AirPrint Enabled	Yes
Office Machine Features	Print from USB flash drive, save to USB flash drive, scan to e-mail, scan to folder, scan to network, scan to Cloud
Localisation	English, German, French, Italian, Spanish / Europe
Memory	
Standard Memory	512 MB
Max Supported Memory	512 MB
Supported Flash Memory	USB flash drive
Copying	
Max Copying Speed	Up to 27 ppm (mono) / up to 27 ppm (colour)
Max Copying Resolution	Up to 600 x 600 dpi (mono) / up to 600 x 600 dpi (colour)
Max Document Enlargement	400%
Max Document Reduction	25%
Maximum Copies	999
Automatic Duplexing	Yes
Copying Features	Collation copy, resize, ID Copy
Printing	



Max Printing Resolution	Up to 38400 x 600 dpi (mono) / up to 38400 x 600 dpi (colour)
Max Printing Speed	Up to 27 ppm (mono) / up to 27 ppm (colour)
Printer Drivers / Emulations	PCL 6, PostScript 3, PCL 5c, PDF, URF, PWG
Image Enhancement Technology	HP ImageREt 3600, Pantone Calibrated
Automatic Duplexing	Yes
First Print Out Time B/W	9.7 sec
First Print Out Time Colour	11.3 sec
Scanning	
Scan Element	CIS
Automatic Duplexing	Yes
Optical Resolution	1200 x 1200 dpi
Grayscale Depth	8-bit
Colour Depth	30-bit
Fax Machine	
Max Transmission Speed	33.6 Kbps
Fax Resolutions	203 x 196 dpi, 300 x 300 dpi, 203 x 96 dpi
Total Memory Capacity	Up to 400 pages
PC Faxing	Yes (send only)
Fax Machine Features	
Speed Dialing	120 station(s)
Delayed Transmission	Yes
Features	Fax forwarding, automatic redialing, junk fax barrier, auto reduction, Distinctive Ring Detection (DRD), fax memory backup, delayed sending, fax polling, block fax, poll receive, fax activity reports, print fax log
Document & Media Handling	
Min Original Size	102 x 152 mm
Max Original Size	Legal (216 x 356 mm)
Original Type	Sheets
Document Feeder Capacity	50 sheets
Min Media Size	76 x 127 mm
Max Media Size	A4/Legal
Min Media Weight	60 g/m ²
Max Media Weight	200 g/m ²
Supported Media Type	Transparencies, envelopes, plain paper, cards, labels, recycled paper, photo paper, bond paper, glossy paper
Supported Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), 100 x 150 mm, 100 x 148 mm, JIS B5 (182 x 257 mm), 101.6 x 152.4 mm, 76 x 127 mm, 215.9 x 330.2 mm, 127 x 203.2 mm
Supported Envelope Sizes	International DL (110 x 220 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm)
Standard Media Capacity	300 sheets
Max Media Capacity	850 sheets
Bypass Feeder Capacity	50 sheets



Output Trays Capacity	150 sheets
Document & Media Handling Details	ADF - 50 sheets - Legal (216 x 356 mm) Input tray - 250 sheets size: 100 x 148 mm - Legal (216 x 356 mm) Bypass tray - 50 sheets size: 76 x 127 mm - Legal (216 x 356 mm) Output tray - 150 sheets
Speed Details	Printing: up to 28 ppm (Letter A) - B/W normal Printing: up to 28 ppm (Letter A) - colour normal Printing: up to 27 ppm (A4) - B/W normal Printing: up to 27 ppm (A4) - colour normal Printing: up to 25 ipm (Letter A) - B/W duplex Printing: up to 25 ipm (Letter A) - colour duplex Printing: up to 24 ipm (A4) - B/W duplex Printing: up to 24 ipm (A4) - colour duplex Copying: up to 28 ppm (Letter A) - B/W normal Copying: up to 28 ppm (Letter A) - colour normal Copying: up to 27 ppm (A4) - B/W normal Copying: up to 27 ppm (A4) - colour normal Copying: up to 25 ipm (Letter A) - colour duplex Copying: up to 25 ipm (Letter A) - B/W duplex Copying: up to 24 ipm (A4) - B/W duplex Copying: up to 24 ipm (A4) - colour duplex Scanning: up to 29 ppm (A4) - B/W normal Scanning: up to 46 ipm (A4) - B/W normal Scanning: up to 20 ppm - colour normal Scanning: up to 35 ipm - colour normal Scanning: up to 46 ipm - B/W duplex Scanning: up to 34 ipm - colour duplex
Connections	
Interfaces	1 x USB 2.0 - 4 pin USB Type B 1 x USB host - 4 pin USB Type A 1 x LAN - RJ-45
Security Protocols & Features	LDAP, SSL, Apple Bonjour, WEP, TLS, WPA, WPA2, 802.1x, TKIP, AES, EAP-TLS, PEAP, WPA2-Enterprise, IPv6 support, SNMP 3
Operating System Support	HP-UX 11.x, SunSoft Solaris 2.5 or later, MS Windows Server 2008 x64 Edition, MS Windows XP SP2 or later, Sun Solaris 8, MS Windows 7, Ubuntu Linux 8.04 LTS, Ubuntu Linux 8.10, Ubuntu Linux 9.04, MS Windows 7 64-bit Edition, MS Windows Vista, MS Windows 2000 Server, MS Windows Vista (64-bit versions), SuSe Linux 10.3, HP-UX 11i, Apple Mac OS X 10.6, Ubuntu Linux 9.10, Ubuntu Linux 10.04, Fedora 10, Fedora 9, Fedora 11, Fedora 12, Ubuntu Linux 8.04.1 LTS, Ubuntu Linux 8.04.2 LTS, Red Hat Linux 7.x or later, SUSE Linux 8.x or later, IBM AIX 3.2.5 or later, Apple Mac OS X 10.7, Debian Linux 5.0, Red Hat Enterprise Linux 5, MS Windows Server 2008 R2 x64 Edition, SuSe Linux 11.0, SuSe Linux 11.1, SuSe Linux 11.2, Debian Linux 5.0.1, Debian Linux 5.0.2, Debian Linux 5.0.3, Oracle Solaris 9, HP-UX 10.20, Apple Mac OS X 10.8, Windows 8, Windows 8 64-bit, MS Windows Server 2012 x64 Edition, MS Windows Server 2003 SP2 or later, MS Windows Server 2003 x64 Edition SP2 or later, Windows 8.1, Apple Mac OS X 10.9, Windows 8.1 64-bit, MS Windows Server 2008 (32/64-bits)
Software Included	Drivers & Utilities, HP Web Jetadmin
Power	
Voltage Required	AC 220 V (50/60Hz)
Power Consumption Operational	550 Watt
Power Consumption Standby	20 Watt
Power Consumption Sleep	0.7 Watt
Miscellaneous	
First Copy Out Time B/W	9.9 sec
First Copy Out Time Colour	12.4 sec
Compliant Standards	FCC Class B certified, CISPR 22 Class B, EN55022 Class B, RSS-210, FCC CFR47 Part 68, FCC CFR47 Part 15, IEC 60950-1, EN 60950-1, FCC CFR47 Part 15 C, GB 9254 Class B, GB 17625.1, EN 62311, EN 61000-3-3:2008, ICES-003 issue 4 Class B, EN 61000-3-2:2006+A1:2009+A2:2009, EN 300 328 V1.7.1, IEC 62479,

IEC 60825-1:2007, EN 62479:2010, IEC 62311, EN 55024:2010, EN 301 489-1,
GB 4943.1-2011, EN 301 489-17

Environmental Standards

ENERGY STAR Certified	Yes
Blue Angel Compliant	Yes

Manufacturer Warranty

Service & Support	Limited warranty - 1 year - on-site - response time: next business day
-------------------	--

Dimensions & Weight

Width	41.6 cm
Depth	47.2 cm
Height	40 cm
Weight	23.4 kg

Dimensions & Weight (Shipping)

Shipping Width	59.7 cm
Shipping Depth	49.7 cm
Shipping Height	49 cm
Shipping Weight	26.8 kg

Environmental Parameters

Sound Emission	49 dBA (operating)
Min Operating Temperature	15 °C
Max Operating Temperature	30 °C
Humidity Range Operating	10 - 80% (non-condensing)