

HPE ProLiant DL360 Gen10 - Server



rack-mountable - 1U - 2-way - 1 x Xeon Gold 6234 / 3.3 GHz - RAM 32 GB - SAS
- hot-swap 2.5" bay(s) - no HDD - GigE - 10 GigE - 25 Gigabit LAN - no OS -
monitor: none

Group	Servers
Manufacturer	HPE
Manufacturer item no.	P19179-B21
EAN/UPC	0190017382401

Description

Does your data center need a secure, performance driven dense server that you can confidently deploy for virtualization, database, or high-performance computing? The HPE ProLiant DL360 Gen10 server delivers security, agility and flexibility without compromise.

Main features

Product Description	HPE ProLiant DL360 Gen10 - rack-mountable - Xeon Gold 6234 3.3 GHz - 32 GB - no HDD
Type	Server - rack-mountable
Height (Rack Units)	1U
Server Scalability	2-way
Processor	1 x Intel Xeon Gold 6234 / 3.3 GHz (4 GHz) (8-core)
Processor Socket	FCLGA3647 Socket
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
Cache Memory	24.75 MB L3 Cache
Cache Per Processor	24.75 MB
RAM	32 GB (installed) / 1.5 TB (max) - DDR4 SDRAM - Advanced ECC
Storage Controller	RAID (SATA 6Gb/s / SAS 12Gb/s) (HPE Smart Array P408i-a)
Server Storage Bays	Hot-swap 2.5"
Hard Drive	No HDD
Optical Storage	No optical drive
Card Reader	Yes
Video Memory	16 MB
Networking	GigE, 10 GigE, 25 Gigabit LAN
Power	AC 120/230 V (50/60 Hz)
Power Redundancy	Optional
OS Provided	No operating system
Dimensions (WxDxH)	43.46 cm x 70.7 cm x 4.29 cm



Weight	13.04 kg
Environmental Standards	ENERGY STAR Qualified

Extended details

General	
Type	Server
Product Form Factor	Rack-mountable - 1U
Server Scalability	2-way
Hot-Swap Bays Qty	8
Processor / Chipset	
CPU	Intel Xeon Gold 6234
Clock Speed	3.3 GHz
Max Turbo Speed	4 GHz
Number of Cores	8-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
CPU Socket	FCLGA3647 Socket
Chipset Type	Intel C621
Cache Memory	
Installed Size	L3 Cache - 24.75 MB
Cache Per Processor	24.75 MB
RAM	
Installed Size	32 GB / 1.5 TB (max)
Technology	DDR4 SDRAM - Advanced ECC
Effective Memory Speed	2933 MHz
Rated Memory Speed	2933 MHz
Form Factor	DIMM 288-pin
Slots	24 (Total) / 23 (empty)
Features	Registered, slots 13 - 24 are available in two-processor configuration only, HPE SmartMemory, 6-channel memory architecture
Configuration Features	1 x 32 GB
RAM Supported	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC
Hard Drive	
Type	No HDD
Storage Controller	
Type	RAID
Controller Interface Type	SATA 6Gb/s / SAS 12Gb/s
Storage Controller Name	HPE Smart Array P408i-a
Channel Qty	8
RAID Level	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, RAID 50, RAID 60, RAID 1 ADM, RAID



	10 ADM
Buffer Size	2 GB
Optical Storage	
Type	No optical drive
Card Reader	
Type	Card reader
Supported Flash Memory Cards	microSD
Monitor	
Monitor Type	None.
Graphics Controller	
Video Memory	16 MB
Video Interfaces	VGA
Networking	
Ethernet Ports	2 x 10/25 Gigabit Ethernet SFP28
Ethernet Controller	HPE 640FLR
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, 10 Gigabit Ethernet, 25 Gigabit Ethernet
Remote Management Protocol	SNMP 3, IPMI 2.0, SMASH CLP
Remote Management Controller	Integrated Lights-Out 5
Features	Wake on LAN (WoL), PXE support
Expansion / Connectivity	
Bays	1 (total) / 1 (free) x external Universal Media Bay ¦ 8 (total) / 8 (free) x hot-swap 2.5" SFF
Slots	1 (total) / 1 (free) x PCIe 3.0 x16 - three-quarter-length, full-height ¦ 1 (total) / 1 (free) x PCIe 3.0 x8 - low-profile ¦ 1 (total) / 1 (free) x FlexibleLOM - three-quarter-length, full-height (low-profile) ¦ 1 (total) / 1 (free) x microSD Card (internal) ¦ 1 (total) / 1 (free) x PCIe x16 - full-height
Interfaces	1 x HPE iLO - Type A (1 in front) ¦ 1 x HPE iLO - RJ-45 (1 rear) ¦ 5 x USB 3.0 (1 front, 2 rear, 2 internal) ¦ 1 x VGA (1 rear) ¦ 2 x LAN (10/25 Gigabit Ethernet) (SFP28)
Miscellaneous	
Included Accessories	5 x standard hot plug fans
Compliant Standards	AES, FIPS 140-2, IPv6 Ready, PCI DSS, TLS v1.2, ASHRAE Class A4, ASHRAE Class A3, WEEE 2002/95/EC, ACPI 6.1
Power	
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	800 Watt
80 PLUS Certification	80 PLUS Platinum
Operating System / Software	
OS Provided	No operating system



OS Certified	CentOS, Microsoft Windows Server 2012 R2, VMware vSphere 6.0 (ESXi), SuSE Linux Enterprise Server 11 SP4, Microsoft Windows Server 2016, Red Hat Enterprise Linux 7.3, Red Hat Enterprise Linux 6.9, VMware vSphere 6.5 (ESXi), SuSE Linux Enterprise Server 12 SP2, ClearOS
--------------	--

Software	HPE Server UEFI
----------	-----------------

Environmental Standards

ENERGY STAR Certified	Yes
-----------------------	-----

ENERGY STAR Version	2.1
---------------------	-----

Manufacturer Warranty

Service & Support	Limited warranty - parts and labour - 3 years - on-site
-------------------	---

Dimensions & Weight

Width	43.46 cm
-------	----------

Depth	70.7 cm
-------	---------

Height	4.29 cm
--------	---------

Weight	13.04 kg
--------	----------

Environmental Parameters

Min Operating Temperature	10 °C
---------------------------	-------

Max Operating Temperature	35 °C
---------------------------	-------

Humidity Range Operating	8 - 90% (non-condensing)
--------------------------	--------------------------

Sound Emission	38.1 dBA
----------------	----------

Technical data © CNET Content Solutions. Subject to technical modifications and errors.