



HPE ProLiant DL360 Gen10 Network Choice

Server - rack-mountable - 1U - 2-way - 1 x Xeon Gold 6250 / 3.9 GHz - RAM 32 GB - SATA/SAS - hot-swap 2.5" bay(s) - no HDD - GigE - no OS - monitor: none

Group	Servers
Manufacturer	HPE
Manufacturer item no.	P40399-B21
EAN/UPC	0190017492209

Description

Does your data center need a secure, performance driven dense server that you can confidently deploy for virtualization, database, or high-performance computing? The HPE ProLiant DL360 Gen10 server delivers security, agility and flexibility without compromise. It supports the Intel Xeon Scalable processor with up to a 60% performance gain and 27% increase in cores, along with 2933 MT/s HPE DDR4 SmartMemory supporting up to 3.0 TB with an increase in performance of up to 82%. With the added performance that HPE Persistent Memory, HPE NVDIMMs and 10 NVMe bring, the HPE ProLiant DL360 Gen10 means business. Deploy, update, monitor and maintain with ease by automating essential server life cycle management tasks with HPE OneView and HPE Integrated Lights Out 5 (iLO 5). Deploy this 2P secure platform for diverse workloads in space constrained environments.

Main features

Product Description	HPE ProLiant DL360 Gen10 Network Choice - rack-mountable - Xeon Gold 6250 3.9 GHz - 32 GB - no HDD
Type	Server - rack-mountable
Height (Rack Units)	1U
Localisation	Region: Worldwide
Server Scalability	2-way
Processor	1 x Intel Xeon Gold 6250 / 3.9 GHz (4.5 GHz) (8-core)
Processor Socket	FCLGA3647 Socket
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
Cache Memory	35.75 MB L3 Cache
Cache Per Processor	35.75 MB
RAM	32 GB (installed) / 1.5 TB (max) - DDR4 SDRAM - Advanced ECC
Storage Controller	SATA (SATA 6Gb/s) (HPE Smart Array S100i)
Server Storage Bays	Hot-swap 2.5"
Hard Drive	No HDD
Optical Storage	No optical drive



Card Reader	Yes
Video Memory	16 MB
Networking	GigE
Power	AC 120/230 V (50/60 Hz)
Power Redundancy	Optional
OS Provided	No operating system
Dimensions (WxDxH)	43.46 cm x 70.7 cm x 4.29 cm
Weight	13.04 kg
Environmental Standards	ENERGY STAR Qualified

Extended details

General	
Type	Server
Product Form Factor	Rack-mountable - 1U
Server Scalability	2-way
Hot-Swap Bays Qty	8
Localisation	Region: Worldwide
Processor / Chipset	
CPU	Intel Xeon Gold 6250
Clock Speed	3.9 GHz
Max Turbo Speed	4.5 GHz
Number of Cores	8-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
CPU Socket	FCLGA3647 Socket
Chipset Type	Intel C621
Cache Memory	
Installed Size	L3 Cache - 35.75 MB
Cache Per Processor	35.75 MB
RAM	
Installed Size	32 GB / 1.5 TB (max)
Technology	DDR4 SDRAM - Advanced ECC
Effective Memory Speed	2933 MHz
Rated Memory Speed	2933 MHz
Form Factor	DIMM 288-pin
Slots	24 (Total) / 23 (empty)
Features	Registered, slots 13 - 24 are available in two-processor configuration only, HPE SmartMemory
Configuration Features	1 x 32 GB
RAM Supported	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC



Hard Drive	
Type	No HDD
Storage Controller	
Type	1 x SATA
Controller Interface Type	SATA 6Gb/s
Storage Controller Name	HPE Smart Array S100i
Channel Qty	14
Optical Storage	
Type	No optical drive
Card Reader	
Type	Card reader
Supported Flash Memory Cards	microSD
Monitor	
Monitor Type	None.
Graphics Controller	
Video Memory	16 MB
Video Interfaces	VGA
Networking	
Ethernet Ports	4 x Gigabit Ethernet
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol	SNMP 3, IPMI 2.0, SMASH CLP
Remote Management Controller	Integrated Lights-Out 5
Features	Wake on LAN (WoL), PXE support
Expansion / Connectivity	
Bays	1 (total) / 1 (free) x external Universal Media Bay 8 (total) / 8 (free) x hot-swap 2.5" SFF
Slots	1 (total) / 1 (free) x PCIe 3.0 x16 - three-quarter-length, full-height 1 (total) / 1 (free) x PCIe 3.0 x8 - low-profile 1 (total) / 1 (free) x FlexibleLOM - three-quarter-length, full-height (low-profile) 1 (total) / 1 (free) x microSD Card (internal) 1 (total) / 1 (free) x PCIe x16 - full-height
Interfaces	1 x HPE iLO - Type A (1 in front) 1 x HPE iLO - RJ-45 (1 rear) 5 x USB 3.0 (1 front, 2 rear, 2 internal) 1 x VGA (1 rear) 4 x LAN (Gigabit Ethernet) - RJ-45 (4 rear)
Miscellaneous	
Compliant Standards	AES, FIPS 140-2, IPv6 Ready, PCI DSS, TLS v1.2, FIPS 201 PIV, ASHRAE Class A4, ASHRAE Class A3, WEEE 2002/95/EC, ACPI 6.1
Power	
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	800 Watt
80 PLUS Certification	80 PLUS Platinum



Operating System / Software

OS Provided	No operating system
OS Certified	CentOS, Microsoft Windows Server 2012 R2, VMware vSphere 6.0 (ESXi), SuSE Linux Enterprise Server 11 SP4, Microsoft Windows Server 2016, Red Hat Enterprise Linux 7.3, Red Hat Enterprise Linux 6.9, VMware vSphere 6.5 (ESXi), SuSE Linux Enterprise Server 12 SP2, ClearOS

Environmental Standards

ENERGY STAR Certified	Yes
ENERGY STAR Version	2.1

Manufacturer Warranty

Service & Support	Limited warranty - parts and labour - 3 years - on-site
-------------------	---

Dimensions & Weight

Width	43.46 cm
Depth	70.7 cm
Height	4.29 cm
Weight	13.04 kg

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90% (non-condensing)
Sound Emission	38.1 dBA

Technical data © CNET Content Solutions. Subject to technical modifications and errors.