

HPE ProLiant DL380 Gen10 SMB Networking Choice

Server - rack-mountable - 2U - 2-way - 1 x Xeon Gold 6248R / 3 GHz
 - RAM 32 GB - SATA - hot-swap 2.5" bay(s) - no HDD - 10 GigE - no OS
 - monitor: none

Group	Servers
Manufacturer	HPE
Manufacturer item no.	P40426-B21
EAN/UPC	0190017492544



Description

The HPE ProLiant DL380 Gen10 server delivers better security, performance and expandability. The HPE ProLiant DL380 Gen10 server is securely designed to reduce costs and complexity. Run everything from the most basic to mission-critical applications and deploy with confidence.

Main features

Product Description	HPE ProLiant DL380 Gen10 SMB Networking Choice - rack-mountable - Xeon Gold 6248R 3 GHz - 32 GB - no HDD
Type	Server - rack-mountable
Height (Rack Units)	2U
Localisation	Region: Worldwide
Server Scalability	2-way
Processor	1 x Intel Xeon Gold 6248R / 3 GHz (4 GHz) (24-core)
Processor Socket	FCLGA3647 Socket
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
Cache Memory	35.75 MB L3 Cache
Cache Per Processor	35.75 MB
RAM	32 GB (installed) / 1.5 TB (max) - DDR4 SDRAM - Advanced ECC
Storage Controller	SATA (SATA 6Gb/s) - PCIe 3.0 x4 (HPE Smart Array S100i SR Software)
Server Storage Bays	Hot-swap 2.5"
Hard Drive	No HDD
Optical Storage	No optical drive
Video Memory	16 MB
Networking	10 GigE
Power	AC 120/230 V (50/60 Hz)
Power Redundancy	Optional
OS Provided	No operating system
Dimensions (WxDxH)	44.55 cm x 73.03 cm x 8.74 cm

Weight	14.76 kg
Environmental Standards	ENERGY STAR Qualified
Extended details	
	General
Type	Server
Product Form Factor	Rack-mountable - 2U
Built-in Devices	Led panel
Server Scalability	2-way
Hot-Swap Bays Qty	8
Localisation	Region: Worldwide
	Processor / Chipset
CPU	Intel Xeon Gold 6248R
Clock Speed	3 GHz
Max Turbo Speed	4 GHz
Number of Cores	24-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
CPU Socket	FCLGA3647 Socket
Chipset Type	Intel C621
	Cache Memory
Installed Size	L3 Cache - 35.75 MB
Cache Per Processor	35.75 MB
	RAM
Installed Size	32 GB / 1.5 TB (max)
Technology	DDR4 SDRAM - Advanced ECC
Effective Memory Speed	2933 MHz
Rated Memory Speed	2933 MHz
Form Factor	DIMM 288-pin
Slots	24 (Total) / 23 (empty)
Features	Registered, dual rank, slots 13 - 24 are available in two-processor configuration only, HPE SmartMemory
Configuration Features	1 x 32 GB
RAM Supported	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC
	Hard Drive
Type	No HDD
	Storage Controller
Type	1 x SATA - PCIe 3.0 x4

Controller Interface Type	SATA 6Gb/s
Storage Controller Name	HPE Smart Array S100i SR Software
Channel Qty	14
RAID Level	RAID 0, RAID 1, RAID 5, RAID 10
	Optical Storage
Type	No optical drive
	Monitor
Monitor Type	None.
	Graphics Controller
Video Memory	16 MB
Video Interfaces	VGA
	Networking
Ethernet Ports	2 x 10 Gigabit Ethernet
Data Link Protocol	10 Gigabit Ethernet
Remote Management Controller	Integrated Lights-Out 5
Features	Wake on LAN (WoL), PXE support
	Expansion / Connectivity
Bays	8 (total) / 8 (free) x hot-swap 2.5" SFF
Slots	1 (total) / 1 (free) x microSD Card (internal) 1 (total) / 1 (free) x PCIe 3.0 x8 - full-length, full-height 1 (total) / 1 (free) x PCIe 3.0 x16 - full-length, full-height 1 (total) / 1 (free) x PCIe 3.0 x8 - half-length, full-height 1 (total) / 0 (free) x FlexibleLOM
Interfaces	3 x USB 3.0 (1 front, 2 rear) 1 x VGA 2 x LAN (10Gigabit Ethernet) (SFP+) 1 x HPE iLO 1 x HPE iLO (service port)
	Miscellaneous
Included Accessories	Cable management arm, 4 standard fans, SFF Easy install rails
Compliant Standards	WEEE, TLS v1.2, low halogen, ASHRAE Class A4, ASHRAE Class A3, WEEE 2002/95/EC, ACPI 6.1
	Power
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	800 Watt
80 PLUS Certification	80 PLUS Platinum
	Operating System / Software
OS Provided	No operating system
	Environmental Standards
ENERGY STAR Certified	Yes

ENERGY STAR Version	3.0
Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 3 years - on-site
Dimensions & Weight	
Width	44.55 cm
Depth	73.03 cm
Height	8.74 cm
Weight	14.76 kg
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.