



HPE ProLiant DL380 Gen10 SMB Networking Choice

Server - rack-mountable - 2U - 2-way - 1 x Xeon Gold 6242 / 2.8 GHz - RAM 32 GB - SATA/SAS - hot-swap 2.5" bay(s) - no HDD - 10 GigE - 25 Gigabit LAN - no OS - monitor: none

Group	Servers
Manufacturer	HPE
Manufacturer item no.	P40428-B21
EAN/UPC	0190017492568

Description

The HPE ProLiant DL380 Gen10 server delivers better security, performance and expandability. The HPE ProLiant DL380 Gen10 server is securely designed to reduce costs and complexity. Run everything from the most basic to mission-critical applications and deploy with confidence.

Main features

Product Description	HPE ProLiant DL380 Gen10 SMB Networking Choice - rack-mountable - Xeon Gold 6242 2.8 GHz - 32 GB - no HDD
Type	Server - rack-mountable
Height (Rack Units)	2U
Localisation	Region: Worldwide
Server Scalability	2-way
Processor	1 x Intel Xeon Gold 6242 / 2.8 GHz (3.9 GHz) (16-core)
Processor Socket	FCLGA3647 Socket
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
Cache Memory	22 MB L3 Cache
Cache Per Processor	22 MB
RAM	32 GB (installed) / 1.5 TB (max) - DDR4 SDRAM - Advanced ECC
Storage Controller	RAID (SATA 6Gb/s / SAS 12Gb/s) (HPE Smart Array P408i-a)
Server Storage Bays	Hot-swap 2.5"
Hard Drive	No HDD
Optical Storage	No optical drive
Card Reader	Yes
Video Memory	16 MB
Networking	10 GigE, 25 Gigabit LAN
Power	AC 120/230 V (50/60 Hz)
Power Redundancy	Optional
OS Provided	No operating system



Dimensions (WxDxH)	44.55 cm x 73.03 cm x 8.74 cm
Weight	14.76 kg
Environmental Standards	ENERGY STAR Qualified

Extended details

General	
Type	Server
Product Form Factor	Rack-mountable - 2U
Server Scalability	2-way
Hot-Swap Bays Qty	8
Localisation	Region: Worldwide
Processor / Chipset	
CPU	Intel Xeon Gold 6242
Clock Speed	2.8 GHz
Max Turbo Speed	3.9 GHz
Number of Cores	16-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
CPU Socket	FCLGA3647 Socket
Chipset Type	Intel C621
Cache Memory	
Installed Size	L3 Cache - 22 MB
Cache Per Processor	22 MB
RAM	
Installed Size	32 GB / 1.5 TB (max)
Technology	DDR4 SDRAM - Advanced ECC
Effective Memory Speed	2933 MHz
Rated Memory Speed	2933 MHz
Form Factor	DIMM 288-pin
Slots	24 (Total) / 23 (empty)
Features	Registered, dual rank, slots 13 - 24 are available in two-processor configuration only, HPE SmartMemory
Configuration Features	1 x 32 GB
RAM Supported	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC
Hard Drive	
Type	No HDD
Storage Controller	
Type	1 x RAID
Controller Interface Type	SATA 6Gb/s / SAS 12Gb/s
Storage Controller Name	HPE Smart Array P408i-a



Channel Qty	8
RAID Level	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, RAID 50, RAID 60, RAID 1 ADM, RAID 10 ADM
Buffer Size	2 GB
Optical Storage	
Type	No optical drive
Card Reader	
Type	Card reader
Supported Flash Memory Cards	microSD
Monitor	
Monitor Type	None.
Graphics Controller	
Video Memory	16 MB
Video Interfaces	VGA
Networking	
Ethernet Ports	2 x 10/25 Gigabit Ethernet SFP28
Data Link Protocol	10 Gigabit Ethernet, 25 Gigabit Ethernet
Remote Management Controller	Integrated Lights-Out 5
Features	Wake on LAN (WoL), PXE support
Expansion / Connectivity	
Bays	8 (total) / 8 (free) x hot-swap 2.5" SFF
Slots	1 (total) / 1 (free) x microSD Card (internal) 1 (total) / 1 (free) x PCIe 3.0 x8 - full-length, full-height 1 (total) / 1 (free) x PCIe 3.0 x16 - full-length, full-height 1 (total) / 1 (free) x PCIe 3.0 x8 - half-length, full-height 1 (total) / 0 (free) x FlexibleLOM
Interfaces	3 x USB 3.0 (1 front, 2 rear) 1 x VGA 2 x LAN (10/25 Gigabit Ethernet) (SFP28) 1 x HPE iLO 1 x HPE iLO (service port)
Miscellaneous	
Included Accessories	Cable management arm, 4 standard fans, SFF Easy install rails
Compliant Standards	WEEE, TLS v1.2, low halogen, ASHRAE Class A4, ASHRAE Class A3, WEEE 2002/95/EC, ACPI 6.1
Power	
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	800 Watt
80 PLUS Certification	80 PLUS Platinum
Operating System / Software	
OS Provided	No operating system
Environmental Standards	
ENERGY STAR Certified	Yes
ENERGY STAR Version	3.0



Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 3 years - on-site
Dimensions & Weight	
Width	44.55 cm
Depth	73.03 cm
Height	8.74 cm
Weight	14.76 kg
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.