HPE OfficeConnect 1405 5G v3 - Switch

unmanaged - 5 x 10/100/1000 - desktop

Group	Network Equipment
Manufacturer	HPE
Manufacturer item no.	JH407A
EAN/UPC	0190017030876

Description

The HPE OfficeConnect 1405 Switch Series consists of Plug-and-Play unmanaged switches designed for small offices, in both Gigabit Ethernet and Fast Ethernet configurations. The 1405 Small Office switches are preconfigured for fast, easy installation, with connections using low-cost Ethernet copper cabling. They support administration-friendly features such as auto-negotiation and automatic cable type detection (MDI/MDIX). The models have energy-saving features such as Energy Efficient Ethernet (EEE) and idle-port power down. All models are fanless for quiet and "green" operation, and are designed for high reliability, long life, low power consumption, and low total cost of ownership.

Main features

Product Description	HPE OfficeConnect 1405 5G v3 - switch - 5 ports - unmanaged
Device Type	Switch - 5 ports - unmanaged
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Switching capacity: 10 Gbps ¦ Throughput: 7.4 Mpps ¦ Latency (100 Mbps): 3 µs ¦ Latency (1000Base-T): 2.6 µs
MAC Address Table Size	2048 entries
Jumbo Frame Support	9216 bytes
Features	Flow control, full duplex capability, Layer 2 switching, auto-uplink (auto MDI/MDI-X), half duplex mode, Quality of Service (QoS), fanless, Energy Efficient Ethernet, 1MB packet buffer, Class of Service (CoS), DiffServ Code Point (DSCP) support
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	11.43 cm x 9.14 cm x 3.56 cm
Weight	180 g

Extended details

	General
Device Type	Switch - 5 ports - unmanaged
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Switching capacity: 10 Gbps ¦ Throughput: 7.4 Mpps ¦ Latency (100 Mbps): 3 µs ¦ Latency (1000Base-T): 2.6 µs
MAC Address Table Size	2048 entries
Jumbo Frame Support	9216 bytes
Features	Flow control, full duplex capability, Layer 2 switching, auto-uplink (auto MDI/MDI-X), half duplex mode, Quality of Service (QoS), fanless, Energy Efficient Ethernet, 1MB packet buffer, Class of Service (CoS), DiffServ Code Point (DSCP) support
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
	Expansion / Connectivity
Interfaces	5 x 1000Base-T RJ-45
	Power
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	3 Watt
	Miscellaneous
Compliant Standards	Plug and Play, UL 60950, EN55022 Class B, ICES-003 Class B, RoHS, IEC 60950-1, EN 60950-1, WEEE, CAN/CSA C22.2 No. 60950-1-03, AS/NZS CISPR 22 Class B, FCC Part 15 Class B
	Dimensions & Weight
Width	11.43 cm
Depth	9.14 cm
Height	3.56 cm
Weight	180 g
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	15 - 95% (non-condensing)
Min Storage Temperature	-40 °C
Max Storage Temperature	70 °C
Humidity Range Storage	15 - 95% (non-condensing)

Technical data © CNET Content Solutions. Subject to technical modifications and errors.