

Iiyama ProLite LH3260HS-B1AG - 32" Diagonal Class (31.5" viewable) LED-backlit LCD display

digital signage - with built-in SoC media player - 1080p 1920 x 1080 - edge-lit - black - matte finish

Group	Digitale Signage
Manufacturer	Iiyama
Manufacturer item no.	LH3260HS-B1AG
EAN/UPC	4948570122288



Description

Enhance visual communication and open up new possibilities for your business with the LH3260HS-B1AG display. This 500cd/m² bright display is a powerful business tool that will take your marketing and communication efforts to the next level. With the Android 11 operating system, iiSignage content management software, Signal FailOver and EShare features, this display offers a simple user experience that makes creating, managing and sharing content a breeze. This ELED VA display consumes significantly less power than DLED IPS displays at the same brightness. Its versatile orientation, sleek design and 24/7 reliability ensure its integration into any business environment. Whether in retail, corporate, hospitality, or education environments, the LH3260HS-B1AG display will undoubtedly captivate audiences and leave a lasting impression.

Main features

Product Description	Iiyama ProLite LH3260HS-B1AG 32" Class (31.5" viewable) LED-backlit LCD display - Full HD - for digital signage
Product Type	LED-backlit LCD flat panel display with built-in SoC media player
Diagonal Class	32"
Diagonal Size	31.5"
Commercial Use	Yes - digital signage
Colour	Black, matte finish
Resolution	1920 x 1080
Display Format	1080p
Frame Rate & Enhancement Technology	60 Hz Frame Rate
Video Interface	HDMI
HDMI Ports Qty	3 ports
Connectivity	Wi-Fi, LAN
Technology	VA
LCD Backlight Technology	Edge-lit LED
Image Aspect Ratio	16:9
TV Tuner	No tuner
Commercial Features	FailOver

Speaker System	2 speakers
Storage Capacity	16 GB
USB	2 ports
Included Accessories	Remote control, screws
Voltage	AC 100-240 V (50/60 Hz)
Energy Class	Class G
Power Consumption Operational	40 Watt
Power Consumption (On mode)	39.5 W
Power Consumption Stand by	0.5 Watt
Dimensions (WxDxH) - without stand	72.46 cm x 4 cm x 41.98 cm
Weight	5.4 kg

Extended details	
	General
Product Type	LED-backlit LCD flat panel display
Energy Class	Class G
Power Consumption Operational	40 Watt
Power Consumption (On mode)	39.5 W
Power Consumption SDR (On mode)	40 kWh/1000h
Diagonal Class	32"
Diagonal Size	31.5"
Commercial Use	Yes - digital signage
Combined With	Built-in SoC media player
Operating System	Android OS 11
TV Tuner	No tuner
TV Tuner Presence	No
Video Interface	HDMI
HDMI Ports Qty	3 ports
Modes	Portrait mode, landscape mode
Design	Fanless Design, metal frame, Thin Bezel Design
Dimensions	Without stand
Width	72.46 cm
Depth	4 cm
Height	41.98 cm
Weight	5.4 kg
Enclosure Colour	Black, matte finish
	Display

LCD Display Technology	VA
Pixel Pitch	0.364 mm
Colour Support	10700000000 colours
Resolution	1920 x 1080
Display Format	1080p
Image Aspect Ratio	16:9
Frame Rate & Enhancement Technology	60 Hz Frame Rate
LCD Backlight Technology	Edge-lit LED
Coating	Anti-glare, 3H Hard, 25% haze
Image Contrast Ratio	4000:1
Brightness	500 cd/m ²
Viewing Angle	178 degrees
Viewing Angle (Vertical)	178 degrees
Response Time	8 ms
Display Menu Language	Czech, English, German, French, Italian, Polish, Russian, Spanish, Dutch, Japanese, Chinese
Commercial Features	FailOver
Operation Hours / Days	24 / 7
Features	Designed for 24/7 operation, Smart Display Module slot, Signal Failover, 8-bit support, Frame Rate Control (FRC), MTBF 50000 hours, iiSignage ² , content management software (CMS)
	Stands & Mounts
Wall Mount Included	Yes
Flat Panel Mount Interface	150 x 200 mm
VESA Compatibility	Yes
	Media Player
USB Port	Yes
USB Ports Qty	2
Configuration	ARM Cortex-A53 Quad-Core - 2 GB - 16 GB - Mali G52 MP2
	Remote Control
Type	Remote control
Battery Included	Yes
	Audio System
Speaker System	2 speakers
Output Power / Total	20 Watt
Speakers	2 x main channel speaker - 10 Watt
	Network & Internet Multimedia
Connectivity	Wi-Fi, LAN

LAN Protocol	Fast Ethernet
Connect & Share	EShare
	Connections
Connector Type	Audio input 3 x HDMI input USB 2.0 2 x RS-232C input LAN Infrared input Audio output
	Miscellaneous
Included Accessories	Screws
Cables Included	RS-232C cable HDMI cable
Compliant Standards	Plug and Play, CB, RoHS, WEEE, REACH, TUV Bauart, ERP, EAC, HDCP 2.2, HDCP 1.4
	Power
Power Device	Power supply
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption Stand by	0.5 Watt
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Dimensions & Weight (Shipping)
Width (Shipping)	79.5 cm
Depth (Shipping)	11.5 cm
Height (Shipping)	52 cm
Weight (Shipping)	7.3 kg
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Technical data © 1WorldSync. Subject to technical modifications and errors.