

Iiyama ProLite T1531SR-B1S - LED monitor

15" - touchscreen - 1024 x 768 - VA - 350 cd/m² - 2500:1 - 18 ms - HDMI
- VGA - DisplayPort - speakers - black - matte

Group	Flat Screens
Manufacturer	Iiyama
Manufacturer item no.	T1531SR-B1S
EAN/UPC	4948570122073



Description

The ProLite T1531SR-B1S was created using five-wire resistive technology. The monitor features an analog D-Sub input and digital HDMI and DisplayPort inputs, and the touchscreen can be connected via USB for great flexibility. The screen's adjustable position (up to 90° upward), combined with the ability to be wall-mounted, makes the panel comfortable and space-saving. The ProLite T1531SR-B1S can be used in a variety of environments, and is especially recommended for stores, restaurants and industrial environments.

Main features

Product Description	Iiyama ProLite T1531SR-B1S - LED monitor - 15"
Device Type	LED-backlit LCD monitor - 15" - touchscreen
Energy Class	Class E
Features	Touch-screen
Panel Type	VA
Aspect Ratio	4:3
Native Resolution	1024 x 768
Pixel Pitch	0.297 mm
Brightness	350 cd/m²
Contrast Ratio	2500:1
Response Time	18 ms (black-to-black)
Input Connectors	HDMI, VGA, DisplayPort
Display Position Adjustments	Tilt
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black, matte
Dimensions (WxDxH)	35.1 cm x 30.65 cm x 20 cm
Weight	4.1 kg
Compliant Standards	VCCI, RoHS, WEEE, cULus, REACH, ERP, EAC, UKCA, IP54 front

Extended details

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	15"
Panel Type	VA
Aspect Ratio	4:3
Native Resolution	1024 x 768
Pixel Pitch	0.297 mm
Brightness	350 cd/m ²
Brightness w/touchscreen	280 cd/m ²
Contrast Ratio	2500:1
Response Time	18 ms (black-to-black)
Horizontal Refresh Rate	31.5 - 60 kHz
Horizontal Viewing Angle	176
Vertical Viewing Angle	176
Backlight Technology	LED backlight
OSD Languages	English, German, French, Italian, Japanese
Features	Cable management cover, HDCP, glove touch mode, stylus touch mode, finger touch mode
Colour	Black, matte
Dimensions (WxDxH)	35.1 cm x 30.65 cm x 20 cm
Weight	4.1 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	1 Watt
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Resistive
Connectivity	
Interfaces	Audio line-out (mini-jack) ¦ HDMI ¦ DisplayPort ¦ VGA
Mechanical	
Display Position Adjustments	Tilt
Tilt Angle	-5/+90
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), 80% light transmittance
Included Accessories	Cable cover
Cables Included	1 x USB cable ¦ 1 x HDMI cable ¦ 1 x audio cable ¦ 1 x DisplayPort cable
Compliant Standards	VCCI, RoHS, WEEE, cULus, REACH, ERP, EAC, UKCA, IP54 front

Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	11 kWh/1000h
Power Consumption (Typical)	16 Watt
Power Consumption Stand by	1.5 Watt
Power Consumption (Off Mode)	0.3 Watt
Software / System Requirements	
OS Required	Linux, Microsoft Windows
Manufacturer Warranty	
Service & Support	Limited warranty - repair - 3 years

Technical data © 1WorldSync. Subject to technical modifications and errors.