

Iiyama ProLite T2755QSC-B1 - LED monitor

27" - touchscreen - 2560 x 1440 WQHD @ 75 Hz - IPS - 400 cd/m² - 1000:1 - 5 ms - HDMI - DisplayPort - speakers - matte black

Group	Flat Screens
Manufacturer	Iiyama
Manufacturer item no.	T2755QSC-B1
EAN/UPC	4948570122981



Description

Iiyama ProLite T2755QSC-B1 - LED monitor - 27" - touchscreen - 2560 x 1440 WQHD @ 75 Hz - IPS - 400 cd/m² - 1000:1 - 5 ms - HDMI, DisplayPort - speakers - matte black

Main features

Product Description	Iiyama ProLite T2755QSC-B1 - LED monitor - 27"
Device Type	LED-backlit LCD monitor - 27" - touchscreen
Energy Class	Class D
Power Consumption (On mode)	17.2 W
Features	Touch-screen, USB 3.2 Gen 1 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	WQHD 2560 x 1440 at 75 Hz
Pixel Pitch	0.233 mm
Brightness	400 cd/m²
Contrast Ratio	1000:1
Response Time	5 ms (grey-to-grey)
Colour Support	16.7 million colours (8-bit)
Input Connectors	HDMI, DisplayPort
Display Position Adjustments	Tilt
Screen Coating	7H Hard Coating, anti-fingerprint
Voltage	AC 100-240 V (50/60 Hz)
Colour	Matte black
Dimensions (WxDxH)	61.4 cm x 4.9 cm x 36.45 cm
Weight	5.8 kg
Compliant Standards	Plug and Play, DDC-2B, DDC/CI, RoHS, WEEE, REACH, TUV Bauart, ERP, EAC, UKCA

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class D
Diagonal Size	27"
Built-in Devices	USB 3.2 Gen 1 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	WQHD 2560 x 1440 at 75 Hz
Pixel Pitch	0.233 mm
Brightness	400 cd/m ²
Brightness w/touchscreen	360 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours (8-bit)
Response Time	5 ms (grey-to-grey)
Horizontal Refresh Rate	30 - 100 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Screen Coating	7H Hard Coating, anti-fingerprint
Backlight Technology	LED backlight
OSD Languages	English, German, French, Italian, Portuguese, Polish, Russian, Spanish, Dutch, Japanese
Features	HDCP, Overdrive technology, edge-to-edge glass, X-Res Technology, Flicker Free technology, Projected Capacitive Touch (P-CAP) technology, i-Style Color, palm rejection function, Blue Light Reducer Function, OSD key lock, +/- 2mm touch accuracy, Eco Mode
Colour	Matte black
Dimensions (WxDxH)	61.4 cm x 4.9 cm x 36.45 cm
Weight	5.8 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	1 Watt
	Input
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
	Connectivity
Interfaces	DisplayPort HDMI 2 x USB 3.2 Gen 1 Audio line-out (mini-jack)
	Mechanical
Display Position Adjustments	Tilt
Tilt Angle	-70/+15

VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), VESA interface support, 90% light transmittance
Included Accessories	Spiral tube
Cables Included	1 x HDMI cable 1 x USB cable
Compliant Standards	Plug and Play, DDC-2B, DDC/CI, RoHS, WEEE, REACH, TUV Bauart, ERP, EAC, UKCA
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	17.2 W
Power Consumption SDR (On mode)	17 kWh/1000h
Power Consumption (Typical)	35 Watt
Power Consumption Stand by	1.5 Watt
Power Consumption (Off Mode)	0.3 Watt
Dimensions & Weight (Shipping)	
Shipping Width	71 cm
Shipping Depth	13 cm
Shipping Height	46 cm
Shipping Weight	7.3 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years - on-site

Technical data © 1WorldSync. Subject to technical modifications and errors.